

# GL720E-2936 Series

## Enhanced Enclosures



Shown with optional accessories

**SHIPPING WEIGHT:** 350 lbs.

**DIMENSIONS:** 72.00"H x 29.00"W x 36.00"D  
Usable inside depth: 34"

**RACK SPACES:** 37 RMU 19" EIA 310-D Compliant

**STOCK COLORS:** Black, Advantage Gray, or Nitro Blue

**WEIGHT CAPACITY:** 1500 lbs. on levelers, bolted to floor, or on heavy duty casters (part no. 7208-EHD)



UL60950-1 Standard for IT & Communications Equipment, Cabinet Enclosures, and Rack Systems

PART NO.	DESCRIPTION
7201E-2936	Base unit with two pairs of black powder coated, universal 19" mounting rails (M6) and package of M6 hardware <small>Note: For 23" mounting, also order part # E23K-36 (conversion kit)</small>
7209-N	Adjustable levelers (2.50"H) - set of 4*
TPE-29P	Removable vented top panel w/two 4.00" horseshoe knock-outs
7202E-29	Plexiglas door with locking swing handle
7204E-29	Perimeter vented steel rear door with locking swing handle
7210-36ELS	Pair of solid lift-off side panels w/lock and finger release latches
7215	16 position power strip w/circuit breaker and 15 ft. cord
<b>GL720E-2936P</b>	<b>Complete enclosure includes items above</b>
GL720E-2936F	Complete enclosure with TPE-29F fan top
GL720E-2936F10	Complete enclosure with TPE-29F10 fan top

### Server Configurations

GL720E-2936MP	Complete enclosure with mesh front & rear doors and TPE-29P vented top
GL720E-2936MCP	Complete enclosure with mesh front door, mesh contour rear door and TPE-29P vented top

## Most Popular Accessories for the GL720E-2936

### PART NO. DESCRIPTION

#### DOORS & SIDE PANELS

7202E-29PV	Perimeter vented plexiglas door
7203E-29	Solid door
7202E-M29	Mesh steel door
7211-36ELL	Pair of locking lift-off vented side panels

Additional Doors & Side Panels: Page 58

#### REMOVABLE TOP & BOTTOM PANELS

TPE-29F	Top panel & fan assembly w/two 4.00" horseshoe knock-outs
TPE-29F10	Top panel & fan assembly w/550 CFM 10" fan & 6 ft. cord
BPF29	Bottom Panel (Filtered) 13"W x 16"D w/rear solid panel for 29"W enclosure
BPS29	Bottom Panel (Solid) 13"W x 16"D w/rear solid panel for 29"W enclosure

Additional Tops & Bottom Panels: Page 60

#### CABLE MANAGEMENT

VLB-7236	Vertical lacing bar kit (includes 1 vertical lacing bar, 2 horizontal lacing bars and 6 CM-01 cinch straps)
HLB-36	Horizontal lacing bar – 36" deep
VLB-72	Extra vertical lacing bar – to be used with lacing bar kit (includes 6 CM-01 cinch straps)

#### 19" RACK MOUNT CABLE MANAGEMENT

CM-04	Interbay cable organizer- 2 RMU
CM-08	Standard front cable organizer- 2 RMU

Additional Cable Management: Page 64

#### STATIONARY SHELVES FOR 19" MOUNTING

7206-FR-AHD	Front & rear mount (adj.) – 22.25"D, Wt. cap.: 200 lbs.
7206-FR-ADHD	Front & rear mount (adj.) – 27.25"D, Wt. cap.: 150 lbs
7206-FR-A32HD	Front & rear mount (adj.) – 32.00"D, Wt. cap. 300 lbs.

Additional Shelves & Shelf Weight Capacities: Page 62

#### SLIDING SHELVES FOR 19" MOUNTING

7206-FRSL-AHD	Front & rear mount sliding (adj.) – 22.00"D, Wt. cap.: 110 lbs.
7206-FRSL-ADHD	Front & rear mount sliding, (adj.) – 26.00"D, Wt. cap.: 110 lbs.
7206-FRSLA300	Front & rear mount sliding, (adj.) – 30.00"D, Wt. cap.: 300 lbs.

Additional Shelves & Shelf Weight Capacities: Page 62

#### SPECIALTY SHELVES FOR 19" MOUNTING

7206-MKM	Monitor/keyboard/mouse shelf
7206-PKB-MT	Pivoting keyboard tray with mouse tray

#### POWER OUTLET STRIPS, COPPER BUS BARS, & COOLING EQUIPMENT

7215-S	16 position power strip w/surge suppressor & 5-15P plug
7215-20ARTLP	20 amp, 16 position power strip w/circuit breaker & twist lock L5-20P plug
7215-20AR	20 amp, 16 position power strip w/circuit breaker & 5-20P plug
CBB-60	Copper bus bar 58" (isolated)
7217FT-3	Front & rear mount, adjustable fan tray w/three 75 CFM fans

Additional Cooling Equipment: Page 63 Additional Power Outlet Strips: Pages 61, 69-72

#### CASTERS, LEVELERS, MOUNTING RAILS, & OTHER ACCESSORIES

7205-ES1P	Pair of 19" mounting rails (tapped) 10/32 w/hardware
7205-ES2P	Pair of 19" EIA mounting rails to accept M6 cage nuts w/hardware
HDW-105-50	Package of 50 M6 cage nuts w/screws – 12mm screw length
E23K-36	Conversion kit to convert from 19" to 23"
AT2	Anti-tip legs
G101	Networking/Ganging kit
AK101	Seismic anchoring kit
7208-E	Castors – one set of four (2 locking and 2 non-locking)
7208-EHD	Heavy Duty Castors – one set of four (all 4 locking) - Wt. Cap.: 1500 lbs.
7209-N4	Adjustable levelers (4.00" in height) – one set of four

\* When casters & levelers are used together, 4" levelers are required.

Additional Accessories: Pages 58-72