


J25564



J7930

## Clamps, Crossover

### Hot Dip Galvanized

#### Joslyn Crossover Clamps For CATV or Telephone Cables

Joslyn's Crossover Clamps are used to clamp two messengers where they cross at right angles.


The J7930 Drop Forged Clamp sections are 1-1/2-inch wide and 3-1/4-inch long. Two 1/2-inch diameter bolts have oval shoulders to prevent turning when tightening.

The J25564 Clamps are 1-1/2-inch wide and 3-1/2-inch long. Two 3/8-inch diameter carriage bolts and nuts are installed in the square holes of the clamp providing a "locking action". Unique cable grooves with a center "dimple" provide superior clamping action.

Catalog No.	For Strand Diameter (Inches)	Approximate Shipping Weight (Lbs. Per 100 Pcs.)
J7930	1/4 to 3/8	154
J25564	3/16 to 1/2	71

## Clamps, Bonding/Grounding

### Hot Dip Galvanized




These grounding clamps are used to attach ground wires at the nut end of shield wire supports as well as other bolts on transmission lines. Catalog number includes two 1-1/2-inch long clamp sections and one square nut.

Catalog No.	Mounting Bolt Size (Inches)	Ground Wire Size (Inches)	Approximate Shipping Weight (Lbs. Per 100 Pcs.)
J1163	5/8	3/16 to 3/8	50
J1164	3/4	1/4 to 1/2	52

## Clamps, Ground Rod

### Bronze Heavy Duty Type



CLAMP WITH HEX HEAD BOLT

Joslyn Bronze Ground Rod Clamps, used with copperbonded ground rods, provide a low resistance, secure copper-to-copper connection. These heavy-duty clamps develop a high-pressure contact between the rod and the grounding wire and can be easily disconnected when it is desired to measure resistance of the ground.

Catalog No. with Hex Head Bolt	Rod Size (Inches)	Size of Grounding Wires Accommodated By Clamp	Approximate Shipping Weight (Lbs. Per 100 Pcs.)
J8490	3/8	6 - 14 AWG	7 - 9
J8491	1/2	2 - 10 AWG	13 - 16
J8492	5/8	1/0 - 8 AWG	15 - 18
J8493	3/4	1/0 - 8 AWG	23 - 26