

Rev: 03/14/22 - A	<b>Structured Cable Products Inc</b>					
<b>USA Warehouses - March 2022</b>						
<b>CONFIDENTIAL</b> All prices are in \$USD and quoted EXW SCP USA Warehouses <b>CONFIDENTIAL</b>						
Prices subject to change without notice. Please confirm prices at time of order.						
<b>BULK CABLES</b>						
<b>Lighting and Control Cables</b>						
<b>Lutron System Compatible Cables</b>						
Features:	Compliance:			Applications:		
Features: Manufactured to exacting specifications. For use with Lutron® and other control systems. UL Plenum and Non-Plenum jacket options. Descending FT and Zone/Outlet Jkt Markings; Spool or Box				Compliance: UL CM CL2/3, c(UL) FT4 75C; UL CMP CL3P c(UL) FT6 75C; 300V; RoHS; UL 444		
Applications: Touch panels, keypads, tuner, audio processors and other control applications. Compatible with Lutron® control systems. Class 2/3 low voltage power.						
SCP Part Number	Construction	Jacket / Color	Installation Rating	Packaged Length		
LUT-BLUE	2C/12AWG BC Str w/Ground + 1C/18AWG BC Str + 2C/22AWG BC Str Shielded	PVC -Blue w/ Dark Blue Stripe	UL CM	152m/500ft Spool		
LUT-BLUE-P	2C/12AWG BC Str w/Ground + 1C/18AWG BC Str + 2C/22AWG BC Str Shielded	Plenum - White w/Blue Stripe	UL CMP	152m/500ft Spool		
LUT-GREEN-P	2C/18AWG BC Str w/Ground + 2C/22AWG BC Str Twisted Pair, Shielded	Plenum - White w/Green Stripe	UL CMP	305m/1000ft Spool		
LUT-GREEN	2C/18AWG BC Str w/Ground + 2C/22AWG BC Str Twisted Pair, Shielded	PVC - Blue w/Green Stripe	UL CM	305m/1000ft Spool		
LUT-GREEN-HDBX	2C/18AWG BC Str w/Ground + 2C/22AWG BC Str Twisted Pair, Shielded	PVC - Blue w/Green Stripe	UL CM	305m/1000ft HD Box		
LUT-QS	2C/16AWG BC Str w/Ground + 2C/22AWG BC Str Twisted Pair, Shielded	PVC - White	UL CM	152m/500ft Spool		
LUT-QS-1000	2C/16AWG BC Str w/Ground + 2C/22AWG BC Str Twisted Pair, Shielded	PVC - White	UL CM	305m/1000ft Spool		
LUT-QS-P	2C/16AWG BC Str w/Ground + 2C/22AWG BC Str Twisted Pair, Shielded	PVC - White	UL CMP	152m/500ft Spool		
LUT-QS-P-1000	2C/16AWG BC Str w/Ground + 2C/22AWG BC Str Twisted Pair, Shielded	PVC - White	UL CMP	305m/1000ft Spool		
<b>Crestron* System Compatible Cables</b>						
Features: Compare to Crestnet® bus cable. UL Plenum and Non-Plenum jacket options. Descending FT and Zone/Outlet Jkt Markings				Compliance: UL CM CL2/3, c(UL) FT4 75C; UL CMP CL3P c(UL) FT6 75C; RoHS		
Applications: Touch panels, keypads, tuner, audio processors and other control applications. Compatible with Crestron® control systems.						
SCP Part Number	Construction	Jacket / Color	Installation Rating	Packaged Length		
CREST-1	2C/18AWG BC Str w/Ground + 2C/22AWG BC Str Twisted Pair, Shielded	PVC - Teal w/Yellow Stripe	UL CM	305m/1000ft Spool		
CREST-1-P	2C/18AWG BC Str w/Ground + 2C/22AWG BC Str FEP Twisted Pair, Shielded	LS-PVC - Teal w/Yellow Stripe	UL CMP	305m/1000ft Spool		
<b>Vantage Compatible Cables</b>						
Features: Vantage compatible lighting/control. 600V rated. Riser rated. Descending FT and Zone/Outlet Jkt Markings				Compliance: UL CMR CL2R/CL3R, c(UL) FT4 75C; 600V; RoHS		
Applications: Lighting bus control. Speaker level audio.						
SCP Part Number	Construction	Jacket / Color	Installation Rating	Packaged Length	Dist Price	
VANTAGE-16/2	2C/16AWG BC Str, 600V rated	PVC - Purple w/Yellow Stripe	UL CMR	305m/1000ft Spool		
<b>Access Control Cables</b>						
Features: Access Control Composite Cables. Overall Jacket. Cost effective security solution. UL Listed. Descending FT and Zone/Outlet Jkt Markings				Compliance: UL CM CL2/3, c(UL) FT4 75C; 300V; RoHS and UL CMP Plenum		
Applications: Low Voltage Security and Control installations. Connectivity for all primary access control components such as card readers, door contacts, etc.						
SCP Part Number	Construction	Jacket / Color	Installation Rating	Packaged Length		
ACC-1	2C/22AWG Str BC + 4C/22AWG Str BC + 6C/22AWG Str BC, Shielded + 4C/18AWG Str BC	PVC - Yellow	UL CM	152m/500ft Spool		
ACC-1-GN	2C/22AWG Str BC + 4C/22AWG Str BC + 6C/22AWG Str BC, Shielded + 4C/18AWG Str BC	PVC - Green	UL CM	152m/500ft Spool		
ACC-1-P	2C/22AWG Str BC + 4C/22AWG Str BC + 6C/22AWG Str BC, Shielded + 4C/18AWG Str BC	Plenum - Yellow	UL CMP	152m/500ft Spool		
<b>Elan Compatible Cables</b>						
Features: Compatible with ELAN home systems bus cable. Composite cable. Descending feet and Zone/Outlet Jkt Markings				Compliance: UL CM CL2/3, c(UL) FT4 75C; ANSI/TIA 568.2-D; RoHS		

Applications: Elan systems bus cable. General purpose security video, LAN.					
SCP Part Number	Construction	Jacket / Color	Installation Rating	Packaged Length	
ELAN-1	RG59/U 20AWG SOL BC + Power: 2C/18AWG + Cat5e 24AWG SOL BC UTP	PVC - Purple	UL CM	152m/500ft Spool	
<b>Coaxial Cables</b>					
<b>RG6/U Quad Shield Coax</b>					
Features: Premium 75 Ohm 3.0GHz Tested Quad (4) Shield Coax, UL Listed, Sun Resistant Jkt; Descending FT and Zone/Outlet Jkt Markings			Compliance: UL TYPE CATV CMP, CMR, CM c(UL); ETL CMR/CM; RoHS; NEC: CATV, CATVR,		
Applications: Audio/Video, CATV, SATV, Antenna					
SCP Part Number	Construction	Jacket / Color	Installation Rating	Packaged Length	
<b>RG6/U Quad Shield Coax - Solid Bare Copper (BC):</b>					
RG6/UQ-P-SPL	18AWG SOL BC F-FEP, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	LS-UV-PVC - White	UL CMP/CL2P	305m/1000ft Spool	
RG6/UQ-BC-BK	18AWG SOL BC F-FEP, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	UV-PVC - Black	UL CM	305m/1000ft Box	
RG6/UQ-BC-BK-5	18AWG SOL BC F-FEP, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	FR-PVC - Black	UL CM	152m/500ft Box	
RG6/UQ-BC-BK-SPL	18AWG SOL BC F-FEP, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	FR-PVC - Black	UL CM	305m/1000ft Spool	
RG6/UQ-BC-WT	18AWG SOL BC F-FEP, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	FR-PVC - White	UL CM	305m/1000ft Box	
RG6/UQ-BC-WT-5	18AWG SOL BC F-FEP, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	FR-PVC - White	UL CM	152m/500ft Box	
RG6/UQ-BC-WT-SPL	18AWG SOL BC F-FEP, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	FR-PVC - White	UL CM	305m/1000ft Spool	
RG6/UQ-S-BC-BK	Dual Coax - 18AWG SOL BC FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%, Siamese (side x side)	FR-PVC - Black	UL CM	152m/500ft Spool	
RG6/UQ-S-BC-WT	Dual Coax - 18AWG SOL BC FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%, Siamese (side x side)	FR-PVC - White	UL CM	152m/500ft Spool	
<b>RG6/U Quad Shield Coax - Solid Copper Clad Steel (CCS):</b>					
RG6/UQ-CCS-BK-ETL-CMR	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	FR-PVC - Black	ETL CMR	305m/1000ft Box	
RG6/UQ-CCS-BK	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	FR-PVC - Black	UL CM	305m/1000ft Box	
RG6/UQ-CCS-BK-SPL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	FR-PVC - Black	UL CM	305m/1000ft Spool	
RG6/UQ-CCS-BK-5	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	FR-PVC - Black	UL CM	152m/500ft Box	
RG6/UQ-CCS-BK-ETL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	FR-PVC - Black	ETL CM	305m/1000ft Box	
RG6/UQ-CCS-BK-ETL-SPL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	FR-PVC - Black	ETL CM	305m/1000ft Spool	
RG6/UQ-CCS-BK-5-ETL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	FR-PVC - Black	ETL CM	152m/500ft Box	
RG6/UQ-CCS-WT	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	FR-PVC - White	UL CM	305m/1000ft Box	
RG6/UQ-CCS-WT-SPL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	FR-PVC - White	UL CM	305m/1000ft Spool	
RG6/UQ-CCS-WT-5	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	FR-PVC - White	UL CM	152m/500ft Box	
RG6/UQ-CCS-WT-ETL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	FR-PVC - White	ETL CM	305m/1000ft Box	
RG6/UQ-CCS-WT-SPL-ETL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	FR-PVC - White	ETL CM	305m/1000ft Spool	
RG6/UQ-CCS-WT-5-ETL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	FR-PVC - White	ETL CM	152m/500ft Box	
RG6/UQ-S-CCS-BK	Dual Coax - 18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%, Siamese (side x side)	FR-PVC - Black	UL CM	152m/500ft Spool	
RG6/UQ-S-CCS-WT	Dual Coax - 18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%, Siamese (side x side)	FR-PVC - White	UL CM	152m/500ft Spool	
<b>RG6/U Tri Shield Coax</b>					
Features: Premium 75 Ohm 3.0GHz Tested Tri Shield Coax, Solid Bare Copper Conductor, UL Listed, Descending M/FT and Zone/Outlet Jkt Markings			Compliance: UL TYPE CATV c(UL) CM; RoHS		
Applications: Audio/Video, CATV					
SCP Part Number	Construction	Jacket / Color	Installation Rating	Packaged Length	

RG6/U-T-CCS-WT-500	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil	FR-PVC - Black	UL CM	152m/500ft Box		
<b>RG6/U Dual Shield Coax</b>						
Features: Premium 75 Ohm 3.0GHz Tested Dual Shield Coax, Solid Bare Copper Conductor, UL Listed, Descending M/FT and Zone/Outlet Jkt Markings			Compliance: UL TYPE CATV c(UL) CM; RoHS			
Applications: Audio/Video, CATV, CCTV transmission						
SCP Part Number	Construction	Jacket / Color	Installation Rating	Packaged Length		
<b>RG6/U Dual Shield Coax - Solid Bare Copper (BC):</b>						
RG6/U-BC-BK	18AWG SOL BC FPE, Bonded CU Foil, 60% AL Braid	FR-PVC - Black	UL CM	305m/1000ft Box		
RG6/U-BC-BK-5	18AWG SOL BC FPE, Bonded CU Foil, 60% AL Braid	FR-PVC - Black	UL CM	152m/500ft Box		
RG6/U-BC-WT	18AWG SOL BC FPE, Bonded CU Foil, 60% AL Braid	FR-PVC - White	UL CM	305m/1000ft Box		
RG6/U-BC-WT-5	18AWG SOL BC FPE, Bonded CU Foil, 60% AL Braid	FR-PVC - White	UL CM	152m/500ft Box		
RG6/U-BC-MES	18AWG SOL BC FPE, Bonded CU Foil, 60% AL Braid + Messenger	FR-PVC - Black	UL CM	152m/500ft Reel in Box		
RG6/U-S-BC-BK	Dual Coax - 2x 18AWG SOL BC FPE, Bonded AL Foil + AL Braid 60%, Siamese (side x side)	FR-PVC - Black	UL CM	152m/500ft Reel in Box		
<b>RG6/U Dual Shield Coax - Solid Copper Clad Steel (CCS):</b>						
RG6/U-P	18AWG SOL CCS F-FEP, Bonded AL Foil + 60% AL Braid	LS-PVC	UL CMP/CL2P	305m/1000ft Spool		
RG6/U-CCS-BK	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	FR-PVC - Black	UL CM	305m/1000ft Box		
RG6/U-CCS-BK-SPL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	FR-PVC - Black	UL CM	305m/1000ft Spool		
RG6/U-CCS-BK-5	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	FR-PVC - Black	UL CM	152m/500ft Box		
RG6/U-CCS-BK-ETL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	FR-PVC - Black	ETL CM	305m/1000ft Box		
RG6/U-CCS-BK-ETL-SPL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	FR-PVC - Black	ETL CM	305m/1000ft Spool		
RG6/U-CCS-BK-5-ETL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	FR-PVC - Black	ETL CM	152m/500ft Box		
RG6/U-CCS-WT	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	FR-PVC - White	UL CM	305m/1000ft Box		
RG6/U-CCS-WT-SPL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	FR-PVC - White	UL CM	305m/1000ft Spool		
RG6/U-CCS-WT-5	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	FR-PVC - White	UL CM	152m/500ft Box		
RG6/U-CCS-WT-ETL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	FR-PVC - White	ETL CM	305m/1000ft Box		
RG6/U-CCS-WT-ETL-SPL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	FR-PVC - White	ETL CM	305m/1000ft Spool		
RG6/U-CCS-WT-5-ETL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	FR-PVC - White	ETL CM	152m/500ft Box		
RG6/U-S-CCS-BK-RIB	Dual Coax - 2x 18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%, Siamese (side x side)	FR-PVC - Black	UL CM	152m/500ft Reel in Box		
<b>RG6/U 95% Coax</b>						
Features: Premium 75 Ohm 3.0GHz Tested Coax, Solid Bare Copper Conductor, 95% BC Braid Shield, UL Listed, Descending M/FT and Zone/Outlet Jkt Markings			Compliance: UL TYPE CATV c(UL) CM; RoHS			
Applications: CCTV transmission, Audio/Video						
SCP Part Number	Construction	Jacket / Color	Installation Rating	Packaged Length		
RG6/U95-BK	18AWG SOL BC FPE, 95% BC Braid	FR-PVC - Black	UL CM	305m/1000ft Box		
RG6/U95-S-BK	18AWG SOL BC FPE, 95% BC Braid + Pwr: 2C/18AWG Str BC,	FR-PVC - Black	UL CM	305m/1000ft Spool		special
RG6/U95-S-BK-500	18AWG SOL BC FPE, 95% BC Braid + Pwr: 2C/18AWG Str BC,	FR-PVC - Black	UL CM	152m/500ft Reel in Box		special
<b>RG11/U Coax</b>						
Features: Premium 75 Ohm 3.0GHz Tested Coax, Solid Bare Copper Conductor, 95% BC Braid Shield, UL Listed, Descending M/FT and Zone/Outlet Jkt Markings			Compliance: UL TYPE CATV c(UL) CM; RoHS			
Applications: CCTV transmission, Audio/Video						
SCP Part Number	Construction	Jacket / Color	Installation Rating	Packaged Length		
RG11/U	14AWG SOL CCS FPE, Bonded AL Foil, 60% AL Braid	FR-PVC - Black	UL CM	305m/1000ft Spool		
RG11/U-DB	14AWG SOL CCS FPE, Bonded AL Foil, 60% AL Braid, Gel Fill	PE - Black	ect Burial/UV Outd	305m/1000ft Spool		
<b>RG59/U Coax</b>						
Features: 75 Ohm CCTV Coax Cable, Solid Bare Copper Conductor, UL Listed, Descending M/FT and Zone/Outlet Jkt Markings			Compliance: UL TYPE CATV c(UL) CM; RoHS			
Applications: Audio/Video, CCTV transmission						
SCP Part Number	Construction	Jacket / Color	Installation Rating	Packaged Length		
<b>RG59/U 95% BC Braid - Nonplenum:</b>						
RG59/U95-BK	20 AWG SOL BC SFPE, 95% BC Braid	FR-PVC - Black	UL CM	305m/1000ft Reel in Box		
RG59/U95-BK-500	20 AWG SOL BC SFPE, 95% BC Braid	FR-PVC - Black	UL CM	152m/500ft Box		
RG59/U95-WT	20 AWG SOL BC SFPE, 95% BC Braid	FR-PVC - White	UL CM	305m/1000ft Reel in Box		

RG59/U95-S-BK	20 AWG SOL BC SFPE 95% BC Braid + Pwr: 2C/18AWG Str BC, Siamese (side x side)	FR-PVC - Black	UL CM	305m/1000ft Spool		
RG59/U95-S-BK-5	20 AWG SOL BC SFPE 95% BC Braid + Pwr: 2C/18AWG Str BC, Siamese (side x side)	FR-PVC - Black	UL CM	152m/500ft Spool		
RG59/U95-S-BK-5-RIB	20 AWG SOL BC SFPE 95% BC Braid + Pwr: 2C/18AWG Str BC, Siamese (side x side)	FR-PVC - Black	UL CM	152m/500ft Reel in Box		
RG59/U95-S-WT	20 AWG SOL BC SFPE 95% BC Braid + Pwr: 2C/18AWG Str BC, Siamese (side x side)	FR-PVC - White	UL CM	305m/1000ft Spool		
RG59/U95-S-WT-5	20 AWG SOL BC SFPE 95% BC Braid + Pwr: 2C/18AWG Str BC, Siamese (side x side)	FR-PVC - White	UL CM	152m/500ft Spool		
RG59/U95-S-WT-5-RIB	20 AWG SOL BC SFPE 95% BC Braid + Pwr: 2C/18AWG Str BC, Siamese (side x side)	FR-PVC - White	UL CM	152m/500ft Reel in Box		
<b>RG59/U Dual Copper Shield - Plenum:</b>						
RG59/U95-P	20 AWG SOL BC F-FEP, 95% BC Braid	LS-PVC - White	UL CMP/CL2P	305m/1000ft Spool		
RG59/U95-S-P	20 AWG SOL BC F-FEP, 95% BC Braid	LS-PVC - White	UL CMP/CL2P	305m/1000ft Spool		
RG59/U95-S-P-500	20 AWG SOL BC F-FEP, 95% BC Braid	LS-PVC - White	UL CMP/CL2P	152m/500ft Spool		
<b>RG59/U Dual Copper Shield - Direct Burial:</b>						
RG59/U95-DB	20 AWG SOL BC SFPE, 95% BC Braid	PE - Black	Direct Burial/Outdoc	305m/1000ft Spool		
<b>RG59/U CCA Braid - Nonplenum:</b>						
RG59/U-CCA-BK-RIB	20 AWG BC SFPE, 95% CCA BRAID	FR-PVC - Black	UL CM	305m/1000ft Reel in Box		
RG59/U-CCA-BK-5-RIB	20 AWG BC SFPE, 95% CCA BRAID	FR-PVC - Black	UL CM	152m/500ft Reel in Box		
RG59/U-CCA-WT-5-RIB	20 AWG BC SFPE, 95% CCA BRAID	FR-PVC - White	UL CM	152m/500ft Reel in Box		
RG59/U-S-CCA-BK	20 AWG SOL BC SFPE, 95% CCA Braid + Pwr: 2C/18AWG Str BC	FR-PVC - Black	UL CM	305m/1000ft Spool		
RG59/U-S-CCA-BK-5	20 AWG SOL BC SFPE, 95% CCA Braid + Pwr: 2C/18AWG Str BC	FR-PVC - Black	UL CM	152m/500ft Spool		
RG59/U-S-CCA-BK-5-RIB	20 AWG SOL BC SFPE, 95% CCA Braid + Pwr: 2C/18AWG Str BC	FR-PVC - Black	UL CM	152m/500ft Reel in Box		
RG59/U-S-CCA-WT	20 AWG SOL BC SFPE, 95% CCA Braid + Pwr: 2C/18AWG Str BC	FR-PVC - White	UL CM	305m/1000ft Spool		
RG59/U-S-CCA-WT-5	20 AWG SOL BC SFPE, 95% CCA Braid + Pwr: 2C/18AWG Str BC	FR-PVC - White	UL CM	152m/500ft Spool		
RG59/U-S-CCA-WT-5-RIB	20 AWG SOL BC SFPE, 95% CCA Braid + Pwr: 2C/18AWG Str BC	FR-PVC - White	UL CM	152m/500ft Reel in Box		
<b>RG59/U CCA Braid - Direct Burial:</b>						
RG59/U-S-DB	20 AWG SOL BC SFPE, 95% CCA Braid, Gel Fill + Pwr: 2C/18AWG Str BC, Siamese	PE - Black	Direct Burial/Outdoc	305m/1000ft Spool		
RG59/U-S-DB-500	20 AWG SOL BC SFPE, 95% CCA Braid, Gel Fill + Pwr: 2C/18AWG Str BC, Siamese	PE - Black	Direct Burial/Outdoc	152m/500ft Spool		
<b>Direct Burial Coax</b>						
Features: Premium 75 Ohm 3.0GHz Tested Quad (4) Shield Coax, UL Listed, Descending M/FT and Zone/Outlet Jkt Markings			Compliance: UL CM; EN50575 CPR Compliant; RoHS			
Applications: Audio/Video, CATV, SATV, Antenna						
SCP Part Number	Construction	Jacket / Color	Installation Rating	Packaged Length		
RG6/UQ-DB	18AWG SOL BC FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%, Gel Filled	PE - Black	Direct Burial/UV Outdoc	305m/1000ft Spool		
RG6/UQ-DB-CCS	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%, Gel Filled	PE - Black	Direct Burial/UV Outdoc	305m/1000ft Spool		
RG6/U-DB	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%, Gel Filled	PE - Black	Direct Burial/UV Outdoc	305m/1000ft Spool		
RG11/U-DB	14AWG SOL CCS FPE, Bonded AL Foil, 60% AL Braid, Gel Fill	PE - Black	Direct Burial/UV Outdoc	305m/1000ft Spool		
<b>Category / LAN Cables</b>						
<b>CAT7A Class Fa</b>						
Features: 1200MHz tested 10GBaseT; Descending FT and Zone/Outlet Jkt Markings; Easy Strip Jacket. Limited Lifetime Warranty			Compliance: ANSI/TIA 568.2-D; ISO/IEC 11801 Class Fa; PoE: IEEE 802.3bt; UL CMR c(UL) FT4; UL 444, UL 1666; RoHS, and a LSZH version			
Applications: High performance IT, LAN & Ethernet installations. Suitable for use in all Class Fa structured wiring systems. PoE/PoH Compliant						
SCP Part Number	AWG	Construction	Jacket / Color	Installation Rating	Packaged Length	
CAT7A-BL	23	4pr S/FTP, SOL BC / SFPE	PVC - Blue	UL CMR/FT4	305m/1000ft Spool	
CAT7A-WT	23	4pr S/FTP, SOL BC / SFPE	PVC - White	UL CMR/FT4	305m/1000ft Spool	
CAT7A-LSZH-XX	23	4pr S/FTP, SOL BC / SFPE	LSZH-XX	ANSI/TIA 568.2	305m/1000ft Spool	
<b>CAT6A Class Ea</b>						

<b>Features:</b> 600MHz tested 10GBaseT; UL Listed; HDBaseT Enhanced; Descending FT and Zone/Outlet Jkt Markings; Limited Lifetime Warranty			<b>Compliance:</b> ANSI/TIA 568.2-D; ISO/IEC 11801 Class Ea; IEC 60332-1-2; PoE,PoH: IEEE 802.3bt; HDBaseT Recommended; UL CMR c(UL) FT4; ETL CMP FT6, CMR FT4; UL 444, UL 1666; RoHS				
<b>Applications:</b> High performance IT, LAN & Ethernet installations. Suitable for use in all Class Ea structured wiring systems. HDBaseT Recommended; PoE/PoH Compliant							
<b>Cat6a Shielded</b>							
SCP Part Number	AWG	Construction	Jacket / Color	Installation Rating	Packaged Length		
CAT6A-SHP-BL	23	4pr U/FTP SOL BC / F-FEP	LS-PVC - Blue	ETL CMP/CL3P	305m/1000ft Spool		
CAT6A-U/FTP-BL	23	4pr U/FTP SOL BC / SFPE	PVC - Blue	UL CMR/FT4	305m/1000ft Spool		
CAT6A-U/FTP-BL-ETL	23	4pr U/FTP SOL BC / SFPE	PVC - Blue	ETL CMR/FT4	305m/1000ft Spool		
CAT6A-U/FTP-WT-ETL	23	4pr U/FTP SOL BC / SFPE	PVC - White	ETL CMR/FT4	305m/1000ft Spool		
CAT6A-F/FTP-BL-ETL	23	4pr U/FTP SOL BC / SFPE	PVC - Blue	ETL CMR/FT4	305m/1000ft Spool		
CAT6A-F/FTP-WT-ETL	23	4pr U/FTP SOL BC / SFPE	PVC - White	ETL CMR/FT4	305m/1000ft Spool		
<b>Cat6a Shielded HDBaseT Enhanced:</b>							
HNCPROPLUS-6A-LSZH	23	4pr U/FTP SOL BC / SFPE	LSZH - Blue	IEC 60332-1-2	305m/1000ft Spool		
<b>Cat6a Shielded Direct Burial:</b>							
CAT6A-U/FTP-DB	23	4pr U/FTP SOL BC / SFPE	LLDPE - Black	Direct Burial/Outdoor	305m/1000ft Spool		
<b>Cat6a Unshielded</b>							
SCP Part Number	AWG	Construction	Jacket / Color	Installation Rating	Packaged Length		
CAT6A-P-BK	23	4pr U/UTP SOL BC / FEP	LS-PVC - Black	UL CMP/CL3P	305m/1000ft Spool		
CAT6A-P-BL	23	4pr U/UTP SOL BC / FEP	LS-PVC - Blue	UL CMP/CL3P	305m/1000ft Spool		
CAT6A-P-WT	23	4pr U/UTP SOL BC / FEP	LS-PVC - White	UL CMP/CL3P	305m/1000ft Spool		
CAT6A	23	4pr U/UTP SOL BC / HDPE	PVC - Blue	UL CMR/FT4	305m/1000ft Spool		
CAT6A-BK	23	4pr U/UTP SOL BC / HDPE	PVC - Black	UL CMR/FT4	305m/1000ft Spool		
CAT6A-GN	23	4pr U/UTP SOL BC / HDPE	PVC - Green	UL CMR/FT4	305m/1000ft Spool		
CAT6A-OR	23	4pr U/UTP SOL BC / HDPE	PVC - Orange	UL CMR/FT4	305m/1000ft Spool		
CAT6A-WT	23	4pr U/UTP SOL BC / HDPE	PVC - White	UL CMR/FT4	305m/1000ft Spool		
CAT6A-YL	23	4pr U/UTP SOL BC / HDPE	PVC - Yellow	UL CMR/FT4	305m/1000ft Spool		
<b>CAT6 Class E</b>							
<b>Features:</b> 550MHz tested 1000BaseT Gigabit; HDBaseT Enhanced; UL Plenum/Riser; UV Sun Resistant; Descending FT and Zone/Outlet Jkt Markings; Packaging: Spool, Reel-in-Box, SCP Tangle-Free Reelex II Boxes; Limited Lifetime Warranty			<b>Compliance:</b> ANSI/TIA 568.2-D; ISO/IEC 11801 Class E; IEC 60332-1-2; PoE,PoH: IEEE 802.3bt; HDBaseT Recommended; UL CMP C(UL) FT6; UL CMR c(UL) FT4; ETL CMP FT6, CMR FT4; UL 444, UL 1666; RoHS				
<b>Applications:</b> High performance IT, LAN & Ethernet installations. Suitable for use in all Class E structured wiring systems. PoE/PoH Compliant							
<b>Cat6 Shielded</b>							
SCP Part Number	AWG	Construction	Jacket / Color	Installation Rating	Packaged Length		
CAT6SHP-BL	23	4pr F/UTP SOL BC / FEP	LS-PVC - Blue	ETL CMP/FT6	305m/1000ft Spool		
CAT6SHP-GY	23	4pr F/UTP SOL BC / FEP	LS-PVC - Gray	ETL CMP/FT6	305m/1000ft Spool		
CAT6SHP-WT	23	4pr F/UTP SOL BC / FEP	LS-PVC - White	ETL CMP/FT6	305m/1000ft Spool		
CAT6SH-BK	23	4pr F/UTP SOL BC / HDPE	PVC - Black	UL CMR/FT4	305m/1000ft Spool		
CAT6SH-BL	23	4pr F/UTP SOL BC / HDPE	PVC - Blue	UL CMR/FT4	305m/1000ft Spool		
CAT6SH-GY	23	4pr F/UTP SOL BC / HDPE	PVC - Gray	UL CMR/FT4	305m/1000ft Spool		
CAT6SH-WT	23	4pr F/UTP SOL BC / HDPE	PVC - White	UL CMR/FT4	305m/1000ft Spool		
<b>Cat6 Shielded HDBaseT Enhanced Indoor/Outdoor Rated:</b>							
HNCPROPLUS-SH-PK	23	4pr F/UTP SOL BC / HDPE	UV Sun Res PVC - Pink	UL CMR/FT4	305m/1000ft Box		
<b>Cat6 Shielded Direct Burial and Outdoor Rated:</b>							
CAT6SH-DB	23	4pr F/UTP SOL BC / HDPE	LLDPE - Black	Direct Burial/UV Outdoor	305m/1000ft Spool		
CAT6SH-OUT	23	4pr F/UTP SOL BC / HDPE	UV Sun Res PE - Black	UV Outdoor	305m/1000ft Spool		
<b>Cat6 Unshielded</b>							
SCP Part Number	AWG	Construction	Jacket / Color	Installation Rating	Packaged Length		
<b>Cat6 Siamese (Side x Side) Unshielded:</b>							
CAT6-S-BL	23	2x 4pr U/UTP SOL BC / HDPE	PVC - Blue	UL CMR/FT4	305m/1000ft Spool		
CAT6-S-WT	23	2x 4pr U/UTP SOL BC / HDPE	PVC - White	UL CMR/FT4	305m/1000ft Spool		
HNCPROPLUS-S-BL	23	2x 4pr U/UTP SOL BC / HDPE	UV Sun Res PVC - Blue	UL CMR/FT4	305m/1000ft Spool		
<b>Cat6 Unshielded Plenum:</b>							
CAT6-P-BK	23	4pr U/UTP SOL BC / FEP	LS-PVC - Black	UL CMP/FT6	305m/1000ft Reel-In-Box		
CAT6-P-BK-ETL	23	4pr U/UTP SOL BC / FEP	LS-PVC - Black	ETL CMP/FT6	305m/1000ft Reel-In-Box		
CAT6-P-BL	23	4pr U/UTP SOL BC / FEP	LS-PVC - Blue	UL CMP/FT6	305m/1000ft Reel-In-Box		

CAT6-P-BL-ETL	23	4pr U/UTP SOL BC / FEP	LS-PVC - Blue	ETL CMP/FT6	305m/1000ft Reel-In-Box		
CAT6-P-GN	23	4pr U/UTP SOL BC / FEP	LS-PVC - Green	UL CMP/FT6	305m/1000ft Reel-In-Box		
CAT6-P-GN-ETL	23	4pr U/UTP SOL BC / FEP	LS-PVC - Green	ETL CMP/FT6	305m/1000ft Reel-In-Box		
CAT6-P-GY	23	4pr U/UTP SOL BC / FEP	LS-PVC - Gray	UL CMP/FT6	305m/1000ft Reel-In-Box		
CAT6-P-PUR	23	4pr U/UTP SOL BC / FEP	LS-PVC - Purple	UL CMP/FT6	305m/1000ft Reel-In-Box		
CAT6-P-WT	23	4pr U/UTP SOL BC / FEP	LS-PVC - White	UL CMP/FT6	305m/1000ft Reel-In-Box		
CAT6-P-WT-ETL	23	4pr U/UTP SOL BC / FEP	LS-PVC - White	ETL CMP/FT6	305m/1000ft Reel-In-Box		
CAT6-P-YL	23	4pr U/UTP SOL BC / FEP	LS-PVC - Yellow	UL CMP/FT6	305m/1000ft Reel-In-Box		
CAT6-P-YL-ETL	23	4pr U/UTP SOL BC / FEP	LS-PVC - Yellow	ETL CMP/FT6	305m/1000ft Reel-In-Box		
<b>Cat6 Unshielded LSZH:</b>							
CAT6-BL-LSZH	23	4pr U/UTP SOL BC / HDPE	LSZH - Blue	IEC 60332-1-2	305m/1000ft Box		
CAT6-GN-LSZH	23	4pr U/UTP SOL BC / HDPE	LSZH - Green	IEC 60332-1-2	305m/1000ft Box		
CAT6-OR-LSZH	23	4pr U/UTP SOL BC / HDPE	LSZH - Orange	IEC 60332-1-2	305m/1000ft Box		
CAT6-WT-LSZH	23	4pr U/UTP SOL BC / HDPE	LSZH - White	IEC 60332-1-2	305m/1000ft Box		
<b>Cat6 Unshielded PVC:</b>							
CAT6-BK	23	4pr U/UTP SOL BC / HDPE	PVC - Black	UL CMR/FT4	305m/1000ft Box		
CAT6-BK-ETL	23	4pr U/UTP SOL BC / HDPE	PVC - Black	ETL CMR/FT4	305m/1000ft Box		
CAT6-BK-HDBX	23	4pr U/UTP SOL BC / HDPE	PVC - Black	UL CMR/FT4	1000ft Heavy Duty Box		
CAT6-BL	23	4pr U/UTP SOL BC / HDPE	PVC - Blue	UL CMR/FT4	305m/1000ft Box		
CAT6-BL-ETL	23	4pr U/UTP SOL BC / HDPE	PVC - Blue	ETL CMR/FT4	305m/1000ft Box		
CAT6-BL-HDBX	23	4pr U/UTP SOL BC / HDPE	PVC - Blue	UL CMR/FT4	1000ft Heavy Duty Box		
CAT6-GN	23	4pr U/UTP SOL BC / HDPE	PVC - Green	UL CMR/FT4	305m/1000ft Box		
CAT6-GN-ETL	23	4pr U/UTP SOL BC / HDPE	PVC - Green	ETL CMR/FT4	305m/1000ft Box		
CAT6-GY	23	4pr U/UTP SOL BC / HDPE	PVC - Gray	UL CMR/FT4	305m/1000ft Box		
CAT6-GY-ETL	23	4pr U/UTP SOL BC / HDPE	PVC - Gray	ETL CMR/FT4	305m/1000ft Box		
CAT6-GY-HDBX	23	4pr U/UTP SOL BC / HDPE	PVC - Gray	UL CMR/FT4	1000ft Heavy Duty Box		
CAT6-OR	23	4pr U/UTP SOL BC / HDPE	PVC - Orange	UL CMR/FT4	305m/1000ft Box		
CAT6-OR-ETL	23	4pr U/UTP SOL BC / HDPE	PVC - Orange	ETL CMR/FT4	305m/1000ft Box		
CAT6-PUR	23	4pr U/UTP SOL BC / HDPE	PVC - Purple	UL CMR/FT4	305m/1000ft Box		
CAT6-PUR-ETL	23	4pr U/UTP SOL BC / HDPE	PVC - Purple	ETL CMR/FT4	305m/1000ft Box		
CAT6-RD	23	4pr U/UTP SOL BC / HDPE	PVC - Red	UL CMR/FT4	305m/1000ft Box		
CAT6-RD-ETL	23	4pr U/UTP SOL BC / HDPE	PVC - Red	ETL CMR/FT4	305m/1000ft Box		
CAT6-WT	23	4pr U/UTP SOL BC / HDPE	PVC - White	UL CMR/FT4	305m/1000ft Box		
CAT6-WT-ETL	23	4pr U/UTP SOL BC / HDPE	PVC - White	ETL CMR/FT4	305m/1000ft Box		
CAT6-WT-HDBX	23	4pr U/UTP SOL BC / HDPE	PVC - White	UL CMR/FT4	1000ft Heavy Duty Box		
CAT6-YL	23	4pr U/UTP SOL BC / HDPE	PVC - Yellow	UL CMR/FT4	305m/1000ft Box		
CAT6-YL-ETL	23	4pr U/UTP SOL BC / HDPE	PVC - Yellow	ETL CMR/FT4	305m/1000ft Box		
<b>Cat6 Unshielded HDBaseT Enhanced Indoor/Outdoor Rated:</b>							
HNCPROPLUS-BK	23	4pr U/UTP SOL BC / HDPE	UV Sun Res PVC - Black	UL CMR/FT4	305m/1000ft Box		
HNCPROPLUS-BL	23	4pr U/UTP SOL BC / HDPE	UV Sun Res PVC - Blue	UL CMR/FT4	305m/1000ft Box		
HNCPROPLUS-GN	23	4pr U/UTP SOL BC / HDPE	UV Sun Res PVC - Green	UL CMR/FT4	305m/1000ft Box		
HNCPROPLUS-GY	23	4pr U/UTP SOL BC / HDPE	UV Sun Res PVC - Gray	UL CMR/FT4	305m/1000ft Box		
HNCPROPLUS-OR	23	4pr U/UTP SOL BC / HDPE	UV Sun Res PVC - Orange	UL CMR/FT4	305m/1000ft Box		
HNCPROPLUS-RD	23	4pr U/UTP SOL BC / HDPE	UV Sun Res PVC - Red	UL CMR/FT4	305m/1000ft Box		
HNCPROPLUS-WT	23	4pr U/UTP SOL BC / HDPE	UV Sun Res PVC - White	UL CMR/FT4	305m/1000ft Box		
HNCPROPLUS-YL	23	4pr U/UTP SOL BC / HDPE	UV Sun Res PVC - Yellow	UL CMR/FT4	305m/1000ft Box		
<b>Cat6 Unshielded Direct Burial:</b>							
CAT6-DB	23	4pr U/UTP SOL BC / HDPE	LLDPE - Black	Direct Burial/UV Outdoor	305m/1000ft Spool		
<b>CAT5E Class D</b>							
<b>Features:</b> 350MHz tested Gigabit Ethernet; HDBaseT Enhanced; UL Plenum/Riser Rated; UV Sun Resistant; Descending FT and Zone/Outlet Jkt Markings ; SCP Tangle-Free Reelx II Boxes; Limited Lifetime Warranty							
<b>Compliance:</b> ANSI/TIA 568.2-D; ISO/IEC 11801 Class D; IEC 60332-1-2; PoE, PoH: IEEE 802.3bt; HDBaseT Recommended; UL CMP c(UL) FT6; UL CMR c(UL) FT4; ETL CMP FT6, CMR FT4; UL 444, UL 1666; RoHS							
<b>Applications:</b> High performance IT, LAN & Ethernet installations. Suitable for use in all Class D structured wiring systems. PoE/PoH Compliant							
<b>Cat5e Shielded</b>							
<b>SCP Part Number</b>	<b>AWG</b>	<b>Construction</b>	<b>Jacket / Color</b>	<b>Installation Rating</b>	<b>Packaged Length</b>		
<b>Cat5e Shielded Plenum:</b>							
CAT5E-SHP-BL	24	4pr F/UTP SOL BC / FEP	LS-PVC - Blue	ETL CMP/FT6	305m/1000ft Box		
CAT5E-SHP-WT	24	4pr F/UTP SOL BC / FEP	LS-PVC - White	ETL CMP/FT6	305m/1000ft Box		

<b>Cat5e Shielded Non-Plenum:</b>					
SCP Part Number	AWG	Construction	Jacket / Color	Installation Rating	Packaged Length
CAT5E-SH-BK	24	4pr F/UTP SOL BC / HDPE	PVC - Black	UL CMR/FT4	305m/1000ft Box
CAT5E-SH-BL	24	4pr F/UTP SOL BC / HDPE	PVC - Blue	UL CMR/FT4	305m/1000ft Box
CAT5E-SH-GY	24	4pr F/UTP SOL BC / HDPE	PVC - Gray	UL CMR/FT4	305m/1000ft Box
CAT5E-SH-WT	24	4pr F/UTP SOL BC / HDPE	PVC - White	UL CMR/FT4	305m/1000ft Box
<b>Cat5e Shielded HDBaseT Enhanced Indoor/Outdoor Rated:</b>					
HNCPRO-SH-PK	24	4pr F/UTP SOL BC / HDPE	UV Sun Res PVC - Pink	UL CMR/FT4	305m/1000ft Box
<b>Cat5e Shielded Direct Burial and Outdoor Rated:</b>					
CAT5E-SH-DB	24	4pr F/UTP SOL BC / HDPE	LLDPE - Black	Direct Burial/UV Outdoor	305m/1000ft Spool
CAT5E-AER	24	24AWG SOL BC / HDPE, w/Messenger	LLDPE - Black	UV Outdoor	305m/1000ft Spool
<b>Cat5e Unshielded</b>					
SCP Part Number	AWG	Construction	Jacket / Color	Installation Rating	Packaged Length
<b>Cat5e 25-Pair Unshielded Non-Plenum:</b>					
CAT5E-25PR	24	25pr U/UTP SOL BC / HDPE	PVC - Blue	UL CMR/FT4	305m/1000ft Spool
CAT5E-25PR-DB	24	25pr U/UTP SOL BC / HDPE	LLDPE - Black	Direct Burial/UV Outdoor	305m/1000ft Spool
<b>Cat5e Unshielded Plenum:</b>					
CAT5E-P-BK	24	4pr U/UTP SOL BC / FEP	LS-PVC - Black	UL CMP/FT6	305m/1000ft Box
CAT5E-P-BL	24	4pr U/UTP SOL BC / FEP	LS-PVC - Blue	UL CMP/FT6	305m/1000ft Box
CAT5E-P-BL-ETL	24	4pr U/UTP SOL BC / FEP	LS-PVC - Blue	ETL CMP/FT6	305m/1000ft Box
CAT5E-P-GN	24	4pr U/UTP SOL BC / FEP	LS-PVC - Green	UL CMP/FT6	305m/1000ft Box
CAT5E-P-GY	24	4pr U/UTP SOL BC / FEP	LS-PVC - Gray	UL CMP/FT6	305m/1000ft Box
CAT5E-P-WT	24	4pr U/UTP SOL BC / FEP	LS-PVC - White	UL CMP/FT6	305m/1000ft Box
CAT5E-P-WT-ETL	24	4pr U/UTP SOL BC / FEP	LS-PVC - White	ETL CMP/FT6	305m/1000ft Box
CAT5E-P-YL	24	4pr U/UTP SOL BC / FEP	LS-PVC - Yellow	UL CMP/FT6	305m/1000ft Box
<b>Cat5e Unshielded Non-Plenum Siamese (Side x Side):</b>					
CAT5E-S-BL	24	2x 4pr U/UTP SOL BC / HDPE	PVC - Blue	UL CMR/FT4	305m/1000ft Box
<b>Cat5e HDBaseT Enhanced Indoor/Outdoor Rated:</b>					
HNCPRO-BL	24	4pr U/UTP SOL BC / FEP	UV Sun Res PVC- Blue	UL CMR/FT4	305m/1000ft Box
HNCPRO-GN	24	4pr U/UTP SOL BC / FEP	UV Sun Res PVC- Green	UL CMR/FT4	305m/1000ft Box
HNCPRO-WT	24	4pr U/UTP SOL BC / FEP	UV Sun Res PVC- White	UL CMR/FT4	305m/1000ft Box
<b>Cat5e Unshielded Non-Plenum PVC:</b>					
CAT5E-BK	24	4pr U/UTP SOL BC / FEP	PVC - Black	UL CMR/FT4	305m/1000ft Box
CAT5E-BK-ETL	24	4pr U/UTP SOL BC / FEP	PVC - Black	ETL CMR/FT4	305m/1000ft Box
CAT5E-BK-HDBX	24	4pr U/UTP SOL BC / FEP	PVC - Black	UL CMR/FT4	1000ft Heavy Duty Box
CAT5E-BLUE	24	4pr U/UTP SOL BC / FEP	PVC - Blue	UL CMR/FT4	305m/1000ft Box
CAT5E-BLUE-5	24	4pr U/UTP SOL BC / FEP	PVC - Blue	UL CMR/FT4	152m/500ft Box
CAT5E-BLUE-5-ETL	24	4pr U/UTP SOL BC / FEP	PVC - Blue	ETL CMR/FT4	152m/500ft Box
CAT5E-BLUE-ETL	24	4pr U/UTP SOL BC / FEP	PVC - Blue	ETL CMR/FT4	305m/1000ft Box
CAT5E-GN	24	4pr U/UTP SOL BC / FEP	PVC - Green	UL CMR/FT4	305m/1000ft Box
CAT5E-GN-5	24	4pr U/UTP SOL BC / FEP	PVC - Green	UL CMR/FT4	152m/500ft Box
CAT5E-GN-5-ETL	24	4pr U/UTP SOL BC / FEP	PVC - Green	ETL CMR/FT4	152m/500ft Box
CAT5E-GN-ETL	24	4pr U/UTP SOL BC / FEP	PVC - Green	ETL CMR/FT4	305m/1000ft Box
CAT5E-GRAY	24	4pr U/UTP SOL BC / FEP	PVC - Gray	UL CMR/FT4	305m/1000ft Box
CAT5E-GRAY-ETL	24	4pr U/UTP SOL BC / FEP	PVC - Gray	ETL CMR/FT4	305m/1000ft Box
CAT5E-OR	24	4pr U/UTP SOL BC / FEP	PVC - Orange	UL CMR/FT4	305m/1000ft Box
CAT5E-OR-ETL	24	4pr U/UTP SOL BC / FEP	PVC - Orange	ETL CMR/FT4	305m/1000ft Box
CAT5E-OR-HDBX	24	4pr U/UTP SOL BC / FEP	PVC - Orange	UL CMR/FT4	1000ft Heavy Duty Box
CAT5E-PK-5-ETL	24	4pr U/UTP SOL BC / FEP	PVC - Pink	ETL CMR/FT4	152m/500ft Box
CAT5E-PUR	24	4pr U/UTP SOL BC / FEP	PVC - Purple	UL CMR/FT4	305m/1000ft Box
CAT5E-PUR-ETL	24	4pr U/UTP SOL BC / FEP	PVC - Purple	ETL CMR/FT4	305m/1000ft Box
CAT5E-RD	24	4pr U/UTP SOL BC / FEP	PVC - Red	UL CMR/FT4	305m/1000ft Box
CAT5E-RD-ETL	24	4pr U/UTP SOL BC / FEP	PVC - Red	ETL CMR/FT4	305m/1000ft Box
CAT5E-WT	24	4pr U/UTP SOL BC / FEP	PVC - White	UL CMR/FT4	305m/1000ft Box
CAT5E-WT-5	24	4pr U/UTP SOL BC / FEP	PVC - White	UL CMR/FT4	152m/500ft Box
CAT5E-WT-5-ETL	24	4pr U/UTP SOL BC / FEP	PVC - White	ETL CMR/FT4	152m/500ft Box
CAT5E-WT-ETL	24	4pr U/UTP SOL BC / FEP	PVC - White	ETL CMR/FT4	305m/1000ft Box
CAT5E-YL	24	4pr U/UTP SOL BC / FEP	PVC - Yellow	UL CMR/FT4	305m/1000ft Box
CAT5E-YL-5	24	4pr U/UTP SOL BC / FEP	PVC - Yellow	ETL CMR/FT4	152m/500ft Box

CAT5E-YL-5-ETL	24	4pr U/UTP SOL BC / FEP	PVC - Yellow	ETL CMR/FT4	152m/500ft Box		
CAT5E-YL-ETL	24	4pr U/UTP SOL BC / FEP	PVC - Yellow	UL CMR/FT4	305m/1000ft Box		
CAT5E-YL-HDBX	24	4pr U/UTP SOL BC / FEP	PVC - Yellow	UL CMR/FT4	1000ft Heavy Duty Box		
<b>Cat5e Unshielded Direct Burial and Outdoor Rated:</b>							
CAT5E-DB	24	4pr U/UTP SOL BC	LLDPE - Black	Direct Burial/UV Outdoor	305m/1000ft Spool		
CAT5E-DB-500	24	4pr U/UTP SOL BC	LLDPE - Black	Direct Burial/UV Outdoor	152m/500ft Spool		
CAT5E-IN/OUT	24	4pr U/UTP SOL BC	UV Sun Res PVC- Black	UL CMR/FT4	305m/1000ft Box		
CAT5E-IN/OUT-WT	24	4pr U/UTP SOL BC	UV Sun Res PVC- White	UL CMR/FT4	305m/1000ft Box		
<b>CAT3 Class C</b>							
<b>Features:</b> 10BaseT Ethernet horizontal premise cable. Suitable for use in all Class C structured wiring systems. Descending FT and Zone/Outlet Jkt Markings. Limited Lifetime Warranty.				<b>Compliance:</b> ANSI/TIA 568.2-D Cat3; ISO/IEC 11801 Class C; UL CMR c(UL) FT4; UL 444 UL 1666; RoHS			
<b>Applications:</b> Telephone, Data & Communications, Telephone Closet Wiring							
<b>SCP Part Number</b>	<b>AWG</b>	<b>Construction</b>	<b>Jacket / Color</b>	<b>Installation Rating</b>	<b>Packaged Length</b>		
CAT3-25PR	24	25PR U/UTP SOL BC / HDPE	PVC - Blue	UL CMR/FT4	305m/1000ft Spool		
CAT3-3PR-GY	24	3pr U/UTP SOL BC / HDPE	PVC - Gray	UL CMR/FT4	305m/1000ft Box		
CAT3-2PR-GY	24	2pr U/UTP SOL BC / HDPE	PVC - Gray	UL CMR/FT4	305m/1000ft Box		
<b>Electrical Low Voltage</b>							
<b>Lighting/Ballast Control Cables</b>							
<b>Features:</b> Low Voltage LED Dimmer Cable. PVC insulated Violet/Gray conductors, twisted pair. 18AWG: Limit to 300ft runs. Riser/Plenum options.				<b>Compliance:</b> NEC: CMR 75°C, CMP 75°C; CEC: FT4 60°C, FT6 60°C; NEC 725, 800. UL 444. RoHS. 300V			
<b>Applications:</b> Low Voltage 0-10V ballast wiring and connections. Low Voltage security & control. Power Limited Control Class 2/Class 3.							
<b>SCP Part Number</b>	<b>AWG</b>	<b>Construction</b>	<b>Jacket / Color</b>	<b>Installation Rating</b>	<b>Packaged Length</b>		
18/2DC-WT-1000	18	2 Cond SOL BC, PVC, TP	PVC - White	CMR FT4	305m/1000ft Spool		
18/2DC-WT-500	18	2 Cond SOL BC, PVC, TP	PVC - White	CMR FT4	152m/500ft Spool		
18/2DC-P-WT-1000	18	2 Cond SOL BC, PVC, TP	LS-PVC - White	CMP FT6	305m/1000ft Spool		
18/2DC-P-WT-500	18	2 Cond SOL BC, PVC, TP	LS-PVC - White	CMP FT6	152m/500ft Spool		
16/2DC-WT-1000	16	2 Cond SOL BC, PVC, TP	PVC - White	CMR FT4	305m/1000ft Spool		
16/2DC-P-WT-1000	16	2 Cond SOL BC, PVC, TP	LS-PVC - White	CMP FT6	305m/1000ft Spool		
<b>Landscape Wire</b>							
<b>Features:</b> Low Voltage Landscape Lighting. Zip Construction.				<b>Compliance:</b> UL Subject 1493, ULECC 150V AC; c(UL) ULEC/LVLL; 150V 60°C			
<b>Applications:</b> Low Voltage landscape lighting, outdoor accent lighting, security lighting. Direct Burial							
<b>SCP Part Number</b>	<b>AWG</b>	<b>Construction</b>	<b>Jacket / Color</b>	<b>Installation Rating</b>	<b>Packaged Length</b>		
16/2L-500	16	2 Cond Str BC, Zip	UV PVC - Black	Outdoor/Direct Burial	152m/500ft Spool		
14/2L-500	14	2 Cond Str BC, Zip	UV PVC - Black	Outdoor/Direct Burial	152m/500ft Spool		
12/2L-500	12	2 Cond Str BC, Zip	UV PVC - Black	Outdoor/Direct Burial	152m/500ft Spool		
10/2L-500	10	2 Cond Str BC, Zip	UV PVC - Black	Outdoor/Direct Burial	152m/500ft Spool		
<b>Thermostat Cables</b>							
<b>Features:</b> Thermostat Wire. Solid Soft Drawn Copper Conductors per ASTM B-3. Polypropylene Insulated. UL 13 CL2R/CL2P. Brown or White Jackets				<b>Compliance:</b> UL and/or ETL. UL 13 Type CL2R, CMR, c(UL) FT4; Plenum: UL CL2P, CMP, c(UL) FT6; NEC 725; UL 1685, 1666; RoHS; 150V 60°C.			
<b>Applications:</b> Thermostats, HVAC controls, Bell & Alarm systems, Signal Systems. Power-Limited Circuits Class 2.							
<b>SCP Part Number</b>	<b>AWG</b>	<b>Construction</b>	<b>Jacket / Color</b>	<b>Installation Rating</b>	<b>Packaged Length</b>		
20/2T-500	20	2 Cond SOL BC	UV PVC - Brown	UL CL2R	152m/500ft Spool		
20/3T-500	20	3 Cond SOL BC	UV PVC - Brown	UL CL2R	152m/500ft Spool		
20/4T-250	20	4 Cond SOL BC	UV PVC - Brown	UL CL2R	250ft Spool		
20/5T-250	20	5 Cond SOL BC	UV PVC - Brown	UL CL2R	250ft Spool		
18/2T	18	2 Cond SOL BC	UV PVC - Brown	UL CL2R	152m/500ft Spool		
18/2T-WT	18	2 Cond SOL BC	UV PVC - Brown	UL CL2R	152m/500ft Spool		
18/3T	18	3 Cond SOL BC	UV PVC - Brown	UL CL2R	152m/500ft Spool		
18/3T-WT	18	3 Cond SOL BC	UV PVC - Brown	UL CL2R	152m/500ft Spool		
18/4T	18	4 Cond SOL BC	UV PVC - Brown	UL CL2R	250ft Spool		
18/4T-WT	18	4 Cond SOL BC	UV PVC - Brown	UL CL2R	250ft Spool		
18/5T	18	5 Cond SOL BC	UV PVC - Brown	UL CL2R	250ft Spool		
18/5T-WT	18	5 Cond SOL BC	UV PVC - Brown	UL CL2R	250ft Spool		

18/5T-500	18	5 Cond SOL BC	UV PVC - Brown	UL CL2R	152m/500ft Spool		
18/6T	18	6 Cond SOL BC	UV PVC - Brown	UL CL2R	250ft Spool		
18/6T-WT	18	6 Cond SOL BC	UV PVC - Brown	UL CL2R	250ft Spool		
18/6T-500	18	6 Cond SOL BC	UV PVC - Brown	UL CL2R	152m/500ft Spool		
18/6T-P-WT	18	6 Cond SOL BC	LS-PVC - White	UL CL2P	250ft Spool		
18/7T	18	7 Cond SOL BC	UV PVC - Brown	UL CL2R	250ft Spool		
18/7T-WT	18	7 Cond SOL BC	UV PVC - Brown	UL CL2R	250ft Spool		
18/8T	18	8 Cond SOL BC	UV PVC - Brown	UL CL2R	250ft Spool		
18/8T-WT	18	8 Cond SOL BC	UV PVC - Brown	UL CL2R	250ft Spool		
18/8T-P-WT	18	8 Cond SOL BC	LS-PVC - White	UL CL2P	250ft Spool		
18/10T	18	10 Cond SOL BC	UV PVC - Brown	UL CL2R	250ft Spool		
18/10T-WT	18	10 Cond SOL BC	UV PVC - Brown	UL CL2R	250ft Spool		

**Ground Wire THHN/THWN**

**Features:** THHN / THWN (Thermoplastic High-Heat Nylon / Thermoplastic Heat-Water Resistant Nylon). **Compliance:** UL-83, UL-1063; VW1, FT1; ASTM-B3, B787, B8; RoHS; 600V 90°C Dry / 75°C wet.

**Applications:** General purpose wiring for appliances, control circuits. Wiring in dry and wet locations.

SCP Part Number	AWG	Construction	Jacket / Color	Installation Rating	Packaged Length		
GW-10-GN	10	1 Cond SOL BC, PVC	UV Nylon - Green	UL 83	152m/500ft Spool		
GW-12-GN	12	1 Cond SOL BC, PVC	UV Nylon - Green	UL 83	152m/500ft Spool		
GW-14-GN	14	1 Cond SOL BC, PVC	UV Nylon - Green	UL 83	152m/500ft Spool		

**Electrical Cord / Power Strip**

SG6-3-WT		6 OUTLET SURGE PROTECTION	WHITE	EACH	3 FOOT CORD		
----------	--	---------------------------	-------	------	-------------	--	--

**Bulk Fiber Cables**

**SCP-EasyFiber™ UltraBendable "Installs Like Copper"**

**Multimode SCP-EasyFiber™ with Corning ClearCurve® OM3 50/125**

SCP-EasyFiber™ with Corning® ClearCurve® is a premium Ultra-Bendable and Laser-Optimized® multimode fiber designed to withstand tight bends and challenging cable routs with substantially less signal loss than conventional multimode fiber cables. Installs "Like Copper"; Saves on Installation Costs. SCP-EasyFiber™ is compatible with industry conventional fiber equipment & standards.

**Features:** UltraBendable and Super Strong. Easy to Install, "Installs Like Copper". UL Listed. Features Corning® ClearCurve® ultra-bendable optical fiber. Descending FT and Zone/Outlet jacket markings. Lightweight and easy to carry. **Compliance:** UL OFNP Plenum FT6 Indoor/Outdoor Rated UV Sun Res Jkt; OFNR Riser FT4. RoHS.

**Applications:** Commercial and Residential LAN, Networking, AV & Digital Signage, Security, and Multi-Dwelling Units.

SCP Part Number	Construction	Packaged Length	
<b>SCP-EasyFiber™ Multimode OM3 50/125, 10G Rated, UL Riser Rated OFNR</b>			
EF-OM3R-DUP-AQ	Duplex Zip OM3 Riser - SCP-EasyFiber™ w/Corning® ClearCurve® - 10G Multimode OM3 50/125, 2.0mm, UL Riser OFNR, Aqua Jkt..	1000FT/305M RIB	
EF-OM3R-4DIST-AQ	4 Strand OM3 Riser SCP-EasyFiber™ w/Corning® ClearCurve® - Tight Buffered Distribution, 10G Multimode OM3 50/125, UL Riser OFNR, Aqua Jkt..	1000FT/305M RIB	
EF-OM3R-6DIST-AQ	6 Strand OM3 Riser SCP-EasyFiber™ w/Corning® ClearCurve® - Tight Buffered Distribution, 10G Multimode OM3 50/125, UL Riser OFNR, Aqua Jkt..	1000FT/305M RIB	
EF-OM3R-6DIST-AQ500	6 Strand OM3 Riser SCP-EasyFiber™ w/Corning® ClearCurve® - Tight Buffered Distribution, 10G Multimode OM3 50/125, UL Riser OFNR, Aqua Jkt..	500ft/152m RIB	
EF-OM3R-12DIST-AQ500	12 Strand OM3 Riser SCP-EasyFiber™ w/Corning® ClearCurve® - Tight Buffered Distribution, 10G Multimode OM3 50/125, UL Riser OFNR, Aqua Jkt..	500ft/152m RIB	
<b>SCP-EasyFiber™ Multimode OM3 50/125, 10G Rated, UL Plenum Rated OFNP, Indoor/Outdoor Rated</b>			
EF-OM3P-2DIST-BK	2 Strand OM3 Plenum SCP-EasyFiber™ w/Corning® ClearCurve® - Tight Buffered Distribution 10G Multimode OM3 50/125, UL Plenum OFNP, Indoor/Outdoor UV Sun Res Black Jacket	1000FT/305M RIB	
EF-OM3P-2DIST-BK-500	2 Strand OM3 Plenum SCP-EasyFiber™ w/Corning® ClearCurve® - Tight Buffered Distribution 10G Multimode OM3 50/125, UL Plenum OFNP, Indoor/Outdoor UV Sun Res Black Jacket	500ft/152m RIB	
EF-OM3P-6DIST-BK	6 Strand OM3 Plenum SCP-EasyFiber™ w/Corning® ClearCurve® - Tight Buffered Distribution 10G Multimode OM3 50/125, UL Plenum OFNP, Indoor/Outdoor UV Sun Res Black Jacket	1000FT/305M RIB	
EF-OM3P-6DIST-BK-500	6 Strand OM3 Plenum SCP-EasyFiber™ w/Corning® ClearCurve® - Tight Buffered Distribution 10G Multimode OM3 50/125, UL Plenum OFNP, Indoor/Outdoor UV Sun Res Black Jacket	500ft/152m RIB	
EF-OM3P-12DIST-BK500	12 Strand OM3 Plenum SCP-EasyFiber™ w/Corning® ClearCurve® - Tight Buffered Distribution 10G Multimode OM3 50/125, UL Plenum OFNP, Indoor/Outdoor UV Sun Res Black Jacket	500ft/152m RIB	

**Note: Above are stock items. Custom Length and Other Multimode Fiber Cables may be available upon request.**

**Single Mode SCP-EasyFiber™ with Corning® SMF-28® Ultra OS2 9/125**

<b>SCP-EasyFiber™ Single Mode with Corning® SMF-28® Ultra delivers the best installation and macrobending performance for Single Mode fiber. SCP-EasyFiber™ Single Mode is a full-spectrum single mode fiber that experiences virtually no signal loss in tight bends and challenging cable routes. Installs "Like Copper"; Saves on Installation Costs. Compatible with conventional industry equipment &amp; standards.</b>						
<b>Features:</b> UltraBendable and Super Strong. Easy to Install, "Installs Like Copper". UL Listed. Features Corning®SMF-28® Ultra OS2 ultra-bendable optical fiber. Descending FT and Zone/Outlet jacket markings. <b>Lightweight and easy to carry box packaging.</b>				<b>Compliance:</b> UL OFNP Plenum FT6 Indoor/Outdoor Rated UV Sun Res Jkt; OFNR Riser FT4, RoHS.		
<b>Applications:</b> Commercial and Residential LAN, Networking, AV & Digital Signage, Security, and Multi-Dwelling Units.						
SCP Part Number	Construction				Packaged Length	
<b>SCP-EasyFiber™ Single Mode OS2 Cables - OS2 9/125, UL Riser Rated OFNR</b>						
EF-OS2R-SIM-WT	Simplex Drop OS2 SCP-EasyFiber™ w/Corning® SMF-28® Ultra - Simplex Single Mode OS2 9/125, 4.8mm, Indoor/Outdoor UL Riser OFNR, UV Sun Res White/Neutral Jacket				2000FT/610M RIB	
EF-OS2R-DUP-YL	Duplex Zip OS2 Riser SCP-EasyFiber™ w/Corning® SMF-28® Ultra - Duplex Single Mode OS2 9/125, 2.0mm, UL Riser OFNR, Yellow Jacket,				2000FT/610M RIB	
EF-OS2R-6DIST-YL1000	6 Strand OS2 Riser SCP-EasyFiber™ w/Corning® SMF-28® Ultra - Tight Buffered Distribution Single Mode OS2 9/125, 2.0mm, UL Riser OFNR, Yellow Jacket,				1000FT/305M RIB	
EF-OS2R-12DIST-YL1000	12 Strand OS2 Riser SCP-EasyFiber™ w/Corning® SMF-28® Ultra - Tight Buffered Distribution Single Mode OS2 9/125, 2.0mm, UL Riser OFNR, Yellow Jacket,				1000FT/305M RIB	
<b>SCP-EasyFiber™ Single Mode OS2 Cables - OS2 9/125, UL Plenum Rated OFNP Indoor/Outdoor Rated</b>						
EF-OS2P-2DIST-BK-1000	2 Strand OS2 Plenum Bend SCP-EasyFiber™ w/Corning® SMF-28® Ultra - Tight Buffered Distribution Single Mode OS2 9/125, UL Plenum OFNP, Indoor/Outdoor UV Sun Res Black Jacket				1000FT/305M RIB	
EF-OS2P-2DIST-BK	2 Strand OS2 Plenum SCP-EasyFiber™ w/Corning® SMF-28® Ultra - Tight Buffered Distribution Single Mode OS2 9/125, UL Plenum OFNP, Indoor/Outdoor UV Sun Res Black Jacket				2000FT/610M RIB	
EF-OS2P-6DIST-BK	6 Strand OS2 Plenum SCP-EasyFiber™ w/Corning® SMF-28® Ultra - Tight Buffered Distribution, Single Mode OS2 9/125, UL Plenum OFNP, Indoor/Outdoor UV Sun Res Black Jacket				2000FT/610M RIB	
EF-OS2P-6DIST-BK-1000	6 Strand OS2 Plenum SCP-EasyFiber™ w/Corning® SMF-28® Ultra - Tight Buffered Distribution, Single Mode OS2 9/125, UL Plenum OFNP, Indoor/Outdoor UV Sun Res Black Jacket				1000FT/305M RIB	
EF-OS2P-12DIST-BK1000	12 Strand OS2 Plenum SCP-EasyFiber™ w/Corning® SMF-28® Ultra - Tight Buffered Distribution, Single Mode OS2 9/125, UL Plenum OFNP, Indoor/Outdoor UV Sun Res Black Jacket				1000FT/305M RIB	
<b>SCP-EasyFiber™ Single Mode Armored OS2 9/125 Tight Buffered Distribution - Indoor/Outdoor Rated</b>						
EF-OS2P-2DISTARM-BK1000	2 Strand Armored OS2 Plenum SCP-EasyFiber™ w/Corning® SMF-28® Ultra, Tight Buffered Distribution, Single Mode OS2 9/125, UL Plenum OFNP, Indoor/Outdoor UV Sun Res Black Jacket				1000FT/305M RIB	
EF-OS2P-6DISTARM-BK1000	6 Strand Armored OS2 Plenum SCP-EasyFiber™ w/Corning® SMF-28® Ultra, Tight Buffered Distribution, Single Mode OS2 9/125, UL Plenum OFNP, Indoor/Outdoor UV Sun Res Black Jacket				1000FT/305M RIB	
<b>Note: Above are stock items. Custom Length and Other Single Mode Fiber Cables may be available upon request.</b>						
<b>Fire Alarm Cables</b>						
<b>FPLR Riser Rated</b>						
<b>Features:</b> Class 2 Circuits and Power Limited Fire Alarm applications. Solid Bare Copper Conductors, Insulated Twisted Pair; UL Listed; Descending Feet Jkt Markings; Packaging: <b>Spool, Box</b>				<b>Compliance:</b> UL FPLR CL2R, c(UL); 18-16AWG: 760 FPLR, 800 CMR; 725 CL2R; 14-12AWG: FPLR, CL2R FT4; RoHS; 300V 60°C		
<b>Applications:</b> Fire Power Limited Riser, Fire Protection Alarm, Monitor/Detection, Signal, Audio Circuits, Control Circuits, Notification & Initiating Circuits						
<b>Unshielded FPLR 300V 75°C</b>						
SCP Part Number	AWG	Construction	Jacket / Color	Installation Rating	Packaged Length	
22/4FPLR	22	4 Cond SOL BC, PVC	PVC - Red	UL FPLR	305m/1000ft Box	
22/4FPLR-COIL	22	4 Cond SOL BC, PVC	PVC - Red	UL FPLR	152m/500ft Coil Pack	
22/4FPLR-500	22	4 Cond SOL BC, PVC	PVC - Red	UL FPLR	152m/500ft Box	
18/2FPLR	18	2 Cond SOL BC, PVC	PVC - Red	UL FPLR	305m/1000ft Spool	
18/2FPLR-BOX	18	2 Cond SOL BC, PVC	PVC - Red	UL FPLR	305m/1000ft Box	
18/2FPLR-500	18	2 Cond SOL BC, PVC	PVC - Red	UL FPLR	152m/500ft Spool	
18/2FPLR-500-BOX	18	2 Cond SOL BC, PVC	PVC - Red	UL FPLR	152m/500ft Box	
18/2FPLR-WT	18	2 Cond SOL BC, PVC	PVC - White	UL FPLR	305m/1000ft Spool	
18/4FPLR	18	4 Cond SOL BC, PVC	PVC - Red	UL FPLR	305m/1000ft Spool	
18/4FPLR-BOX	18	4 Cond SOL BC, PVC	PVC - Red	UL FPLR	305m/1000ft Box	
18/4FPLR-500	18	2 Cond SOL BC, PVC	PVC - Red	UL FPLR	152m/500ft Box	
18/4FPLR-WT	18	2 Cond SOL BC, PVC	PVC - White	UL FPLR	305m/1000ft Spool	
16/2FPLR	16	2 Cond SOL BC, PVC	PVC - Red	UL FPLR	305m/1000ft Spool	
16/2FPLR-BOX	16	2 Cond SOL BC, PVC	PVC - Red	UL FPLR	305m/1000ft Box	
16/2FPLR-500	16	2 Cond SOL BC, PVC	PVC - Red	UL FPLR	152m/500ft Box	
16/2FPLR-BL	16	2 Cond SOL BC, PVC	PVC - Blue	UL FPLR	305m/1000ft Spool	
16/2FPLR-GN	16	2 Cond SOL BC, PVC	PVC - Green	UL FPLR	305m/1000ft Spool	
16/2FPLR-WT	16	2 Cond SOL BC, PVC	PVC - White	UL FPLR	305m/1000ft Spool	
16/4FPLR	16	4 Cond SOL BC, PVC	PVC - Red	UL FPLR	305m/1000ft Spool	
14/2FPLR	14	2 Cond SOL BC, PVC	PVC - Red	UL FPLR	305m/1000ft Spool	
14/2FPLR-500	14	2 Cond SOL BC, PVC	PVC - Red	UL FPLR	152m/500ft Spool	

14/2FPLR-BL	14	2 Cond SOL BC, PVC	PVC - Blue	UL FPLR	305m/1000ft Spool		
14/2FPLR-OR	14	2 Cond SOL BC, PVC	PVC - Orange	UL FPLR	305m/1000ft Spool		
14/2FPLR-WT	14	2 Cond SOL BC, PVC	PVC - White	UL FPLR	305m/1000ft Spool		
14/2FPLR-YL	14	2 Cond SOL BC, PVC	PVC - Yellow	UL FPLR	305m/1000ft Spool		
14/2FPLR-YL-500	14	2 Cond SOL BC, PVC	PVC - Yellow	UL FPLR	152m/500ft Spool		
14/4FPLR	14	4 Cond SOL BC, PVC	PVC - Red	UL FPLR	305m/1000ft Spool		
12/2FPLR	12	2 Cond SOL BC, PVC	PVC - Red	UL FPLR	305m/1000ft Spool		
<b>Shielded FPLR 300V 75°C</b>							
SCP Part Number	AWG	Construction	Jacket / Color	Installation Rating	Packaged Length		
18/2FPLR-SH	18	2 Cond SOL BC, AL Foil, PVC	PVC - Red	UL FPLR	305m/1000ft Spool		
18/4FPLR-SH	18	4 Cond SOL BC, AL Foil, PVC	PVC - Red	UL FPLR	305m/1000ft Spool		
16/2FPLR-SH	16	2 Cond SOL BC, AL Foil, PVC	PVC - Red	UL FPLR	305m/1000ft Spool		
16/2FPLR-SH-OR	16	2 Cond SOL BC, AL Foil, PVC	PVC - Orange	UL FPLR	305m/1000ft Spool		
16/2FPLR-SH-WT	16	2 Cond SOL BC, AL Foil, PVC	PVC - White	UL FPLR	305m/1000ft Spool		
16/4FPLR-SH	16	4 Cond SOL BC, AL Foil, PVC	PVC - Red	UL FPLR	305m/1000ft Spool		
14/2FPLR-SH	14	2 Cond SOL BC, AL Foil, PVC	PVC - Red	UL FPLR	305m/1000ft Spool		
<b>FPLR Plenum Rated</b>							
<b>Features:</b> Stranded or Solid Bare Copper Conductors, Insulated Twisted Pair; UL Listed; Descending Feet and Zone/Outlet Jkt Markings ; Packaging: Spool, SCP Tangle-Free Reellex II Boxes				<b>Compliance:</b> UL FPLR CL2P, c(UL); 18-16AWG: 760 FPLP, 800 CMP; 725 CL2P; 14-12AWG: FPLP, CL2P FT6; RoHS; 300V 60°C			
<b>Applications:</b> Fire Power Limited Plenum, Fire Protection Alarm, Monitor/Detection, Signal, Audio Circuits, Control Circuits, Notification & Initiating Circuits							
<b>Unshielded FPLP (Plenum) 300V 75°C</b>							
SCP Part Number	AWG	Construction	Jacket / Color	Installation Rating	Packaged Length		
18/2FPLP	18	2 Cond SOL BC, LS-PVC	LS-PVC - Red	UL FPLP	305m/1000ft Spool		
18/4FPLP	18	4 Cond SOL BC, LS-PVC	LS-PVC - Red	UL FPLP	305m/1000ft Spool		
16/2FPLP	16	2 Cond SOL BC, LS-PVC	LS-PVC - Red	UL FPLP	305m/1000ft Spool		
16/2FPLP-500	16	2 Cond SOL BC, LS-PVC	LS-PVC - Red	UL FPLP	152m/500ft Spool		
16/2FPLP-BL	16	2 Cond SOL BC, LS-PVC	LS-PVC - Blue	UL FPLP	305m/1000ft Spool		
16/2FPLP-GN	16	2 Cond SOL BC, LS-PVC	LS-PVC - Green	UL FPLP	305m/1000ft Spool		
16/2FPLP-WT	16	2 Cond SOL BC, LS-PVC	LS-PVC - White	UL FPLP	305m/1000ft Spool		
16/2FPLP-YL	16	2 Cond SOL BC, LS-PVC	LS-PVC - Yellow	UL FPLP	305m/1000ft Spool		
16/4FPLP	16	4 Cond SOL BC, LS-PVC	LS-PVC - Red	UL FPLP	305m/1000ft Spool		
16/4FPLP-250	16	4 Cond SOL BC, LS-PVC	LS-PVC - Red	UL FPLP	76m/250ft Spool		
14/2FPLP	14	2 Cond SOL BC, LS-PVC	LS-PVC - Red	UL CL2P	305m/1000ft Spool		
14/2FPLP-500	14	2 Cond SOL BC, LS-PVC	LS-PVC - Red	UL CL2P	152m/500ft Box		
14/2FPLP-BL	14	2 Cond SOL BC, LS-PVC	LS-PVC - Blue	UL CL2P	305m/1000ft Spool		
14/2FPLP-GN	14	2 Cond SOL BC, LS-PVC	LS-PVC - Green	UL CL2P	305m/1000ft Spool		
14/2FPLP-OR	14	2 Cond SOL BC, LS-PVC	LS-PVC - Orange	UL CL2P	305m/1000ft Spool		
14/2FPLP-WT	14	2 Cond SOL BC, LS-PVC	LS-PVC - White	UL CL2P	305m/1000ft Spool		
14/2FPLP-YL	14	2 Cond SOL BC, LS-PVC	LS-PVC - Yellow	UL CL2P	305m/1000ft Spool		
14/4FPLP	14	4 Cond SOL BC, LS-PVC	LS-PVC - Red	UL CL2P	305m/1000ft Spool		
12/2FPLP	12	2 Cond SOL BC, LS-PVC	LS-PVC - Red	UL CL2P	305m/1000ft Spool		
12/2FPLP-STR	12	2 Cond STR BC, LS-PVC	LS-PVC - Red	UL CL2P	305m/1000ft Spool		
<b>Shielded FPLP (Plenum) 300V 75°C</b>							
SCP Part Number	AWG	Construction	Jacket / Color	Installation Rating	Packaged Length		
18/2FPLP-SH	18	2 Cond SOL BC, LS-PVC, AL Foil	LS-PVC - Red	UL FPLP	305m/1000ft Spool		
18/4FPLP-SH	18	4 Cond SOL BC, LS-PVC, AL Foil	LS-PVC - Red	UL FPLP	305m/1000ft Spool		
16/2FPLP-SH	16	2 Cond SOL BC, LS-PVC, AL Foil	LS-PVC - Red	UL FPLP	305m/1000ft Spool		
16/2FPLP-SH-WT	16	2 Cond SOL BC, LS-PVC, AL Foil	LS-PVC - White	UL FPLP	305m/1000ft Spool		
16/4FPLP-SH	16	4 Cond SOL BC, LS-PVC, AL Foil	LS-PVC - Red	UL FPLP	305m/1000ft Spool		
14/2FPLP-SH	14	2 Cond SOL BC, LS-PVC, AL Foil	LS-PVC - Red	UL CL2P	305m/1000ft Spool		
<b>Multi-Purpose - Audio, Communication &amp; Control Cables</b>							
<b>Analog Audio Cables</b>							
<b>Features:</b> Balanced line level audio and control. Superior signal-to-noise ratio. Riser rated. Descending FT and Zone/Outlet Jkt Markings. SCP Tangle-Free Reellex II Box.				<b>Compliance:</b> UL CMR CL2R/CL3R, c(UL) FT4; RoHS; Low Voltage & Power Limited Systems; 300V 75°C			

<b>Applications:</b> High performing audio and control distribution. Permanent or Semi-Permanent Installations. Microphone/Intercom Distribution. Sound/Audio Systems. Security and Power-Limited Control Controls.							
SCP Part Number	Construction		Jacket / Color	Installation Rating	Packaged Length		
22/2ESH	2C/22AWG BC Str Twisted Pair w/Drain, Shielded		PVC - Gray	UL CMR	305m/1000ft Box		
22/4EPSH	(2) Pair 22AWG BC Str Twisted Pair w/Drain, Ea Pair Shielded		PVC - Gray	UL CMR	305m/1000ft Box		
<b>Multi-Purpose Non-Plenum</b>							
<b>Features:</b> Stranded or Solid Bare Copper Conductors, Insulated Twisted Pair; UL Listed; Descending Feet and Zone/Outlet Jkt Markings; Packaging: Spool/Box			<b>Compliance:</b> UL CMR CL2R/CL3R, c(UL) FT4; UL 444; NEC 725, 800; RoHS; Low Voltage & Power Limited Systems; 300V 75°C				
<b>Applications:</b> Low Voltage Security & Control; Intercom Systems; Sound/Audio Systems; 70V Speaker; Power-Limited Controls Class 2 and Class 3							
<b>Non-Plenum - Riser Unshielded</b>							
SCP Part Number	AWG	Construction	Jacket / Color	Installation Rating	Packaged Length		
18/2-GY	18	2 Cond/16 Str BC, PVC	PVC - Gray	UL CMR	305m/1000ft Box		
18/2-GY-500	18	2 Cond/16 Str BC, PVC	PVC - Gray	UL CMR	152m/500ft Box		
18/2-WT	18	2 Cond/16 Str BC, PVC	PVC - White	UL CMR	305m/1000ft Box		
18/2-WT-500	18	2 Cond/16 Str BC, PVC	PVC - White	UL CMR	152m/500ft Box		
18/4-GY	18	4 Cond/16 Str BC, PVC	PVC - Gray	UL CMR	305m/1000ft Box		
18/4-GY-500	18	4 Cond/16 Str BC, PVC	PVC - Gray	UL CMR	152m/500ft Box		
18/4-WT	18	4 Cond/16 Str BC, PVC	PVC - White	UL CMR	305m/1000ft Box		
18/4-WT-500	18	4 Cond/16 Str BC, PVC	PVC - White	UL CMR	152m/500ft Box		
18/6-GY	18	6 Cond/16 Str BC, PVC	PVC - Gray	UL CMR	305m/1000ft Spool		
18/6-GY-500	18	6 Cond/16 Str BC, PVC	PVC - Gray	UL CMR	152m/500ft Box		
16/2-GY	16	2 Cond/26 Str BC, PVC	PVC - Gray	UL CMR	305m/1000ft Box		
16/4-GY	16	4 Cond/26 Str BC, PVC	PVC - Gray	UL CMR	305m/1000ft Box		
14/2-GY	14	2 Cond/19 Str BC, PVC	PVC - Gray	UL CL2R/CL3R	305m/1000ft Spool		
14/4-GY	14	4 Cond/19 Str BC, PVC	PVC - Gray	UL CL2R/CL3R	305m/1000ft Spool		
<b>Non-Plenum - Riser Shielded</b>							
SCP Part Number	AWG	Construction	Jacket / Color	Installation Rating	Packaged Length		
22/2SH-GY	22	2 Cond/7 Str BC, PVC, AL Foil	PVC - Gray	UL CMR	305m/1000ft Box		
22/4SH-GY	22	4 Cond/7 Str BC, PVC, AL Foil	PVC - Gray	UL CMR	305m/1000ft Box		
22/4SH-GY-500	22	4 Cond/7 Str BC, PVC, AL Foil	PVC - Gray	UL CMR	152m/500ft Box		
22/6SH-GY	22	6 Cond/7 Str BC, PVC, AL Foil	PVC - Gray	UL CMR	305m/1000ft Box		
22/6SH-500	22	6 Cond/7 Str BC, PVC, AL Foil	PVC - Gray	UL CMR	152m/500ft Box		
22/6SH-WT	22	6 Cond/7 Str BC, PVC, AL Foil	PVC - Gray	UL CMR	305m/1000ft Box		
22/8SH-GY	22	8 Cond/7 Str BC, PVC, AL Foil	PVC - Gray	UL CMR	305m/1000ft Box		
22/8SH-WT	22	8 Cond/7 Str BC, PVC, AL Foil	PVC - Gray	UL CMR	305m/1000ft Box		
18/2SH-GY	18	2 Cond/16 Str BC, PVC, AL Foil	PVC - Gray	UL CMR	305m/1000ft Box		
18/4SH-GY	18	4 Cond/16 Str BC, PVC, AL Foil	PVC - Gray	UL CMR	305m/1000ft Spool		
18/4SH-GY-500	18	4 Cond/16 Str BC, PVC, AL Foil	PVC - Gray	UL CMR	152m/500ft Box		
18/6SH-GY	18	6 Cond/16 Str BC, PVC, AL Foil	PVC - Gray	UL CMR	305m/1000ft Spool		
18/6SH-GY-500	18	6 Cond/16 Str BC, PVC, AL Foil	PVC - Gray	UL CMR	152m/500ft Box		
18/8SH-GY	18	8 Cond/16 Str BC, PVC, AL Foil	PVC - Gray	UL CMR	305m/1000ft Spool		
16/2SH-GY	16	2 Cond/26 Str BC, PVC, AL Foil	PVC - Gray	UL CMR	305m/1000ft Box		
16/4SH-GY	16	4 Cond/26 Str BC, PVC, AL Foil	PVC - Gray	UL CMR	305m/1000ft Spool		
14/2SH-GY	14	2 Cond/19 Str BC, PVC, AL Foil	PVC - Gray	UL CL2R/CL3R	305m/1000ft Spool		
14/4SH-GY	14	4 Cond/19 Str BC, PVC, AL Foil	PVC - Gray	UL CL2R/3R	305m/1000ft Spool		
<b>Multi-Purpose Plenum</b>							
<b>Features:</b> Stranded or Solid Bare Copper Conductors, Insulated Twisted Pair; UL Listed; Descending Feet and Zone/Outlet Jkt Markings; Packaging: Spool or Box			<b>Compliance:</b> UL CMP c(UL) FT6; 22-16AWG: FPLP/760, CMP 800, CL3P, CL2P/725; 14-12AWG: FPLP, CL3P; UL 444; RoHS; Low Voltage & Power Limited Systems; 300V 75°C; 14-12AWG are not recognized by c(UL).				
<b>Applications:</b> Low Voltage Security & Control; Intercom Systems; Sound/Audio Systems; 70V Speaker; Power-Limited Controls Class 2 and Class 3							
<b>Plenum - UnShielded</b>							
SCP Part Number	AWG	Construction	Jacket / Color	Installation Rating	Packaged Length		
22/2P	22	2 Cond/7 Str BC, LS-PVC	LS-PVC - White	UL CMP	305m/1000ft Box		
22/4P	22	4 Cond/7 Str BC, LS-PVC	LS-PVC - White	UL CMP	305m/1000ft Box		
22/4P-500	22	4 Cond/7 Str BC, LS-PVC	LS-PVC - White	UL CMP	152m/500ft Box		
22/6P	22	6 Cond/7 Str BC, LS-PVC	LS-PVC - White	UL CMP	305m/1000ft Spool		

22/6P-500	22	6 Cond/7 Str BC, LS-PVC	LS-PVC - White	UL CMP	152m/500ft Box		
22/12P	22	12 Cond/7 Str BC, LS-PVC	LS-PVC - White	UL CMP	305m/1000ft Spool		
18/2P	18	2 Cond/7 Str BC, LS-PVC	LS-PVC - White	UL CMP	305m/1000ft Spool		
18/2P-500	18	2 Cond/7 Str BC, LS-PVC	LS-PVC - White	UL CMP	152m/500ft Box		
18/4P	18	4 Cond/7 Str BC, LS-PVC	LS-PVC - White	UL CMP	305m/1000ft Spool		
18/4P-500	18	4 Cond/7 Str BC, LS-PVC	LS-PVC - White	UL CMP	152m/500ft Box		
18/6P	18	6 Cond/7 Str BC, LS-PVC	LS-PVC - White	UL CMP	305m/1000ft Spool		
18/8P	18	8 Cond/7 Str BC, LS-PVC	LS-PVC - White	UL CMP	305m/1000ft Spool		
16/2P	16	2 Cond/19 Str BC, LS-PVC	LS-PVC - White	UL CMP	305m/1000ft Spool		
16/2P-BK	16	2 Cond/19 Str BC, LS-PVC	LS-PVC - Black	UL CMP	305m/1000ft Spool		
16/4P	16	4 Cond/19 Str BC, LS-PVC	LS-PVC - White	UL CMP	305m/1000ft Spool		
16/4P-BK	16	4 Cond/19 Str BC, LS-PVC	LS-PVC - Black	UL CMP	305m/1000ft Spool		
14/2P	14	2 Cond/19 Str BC, LS-PVC	LS-PVC - White	UL FPLP, CL3P	305m/1000ft Spool		
14/2P-500-BOX	14	2 Cond/19 Str BC, LS-PVC	LS-PVC - White	UL FPLP, CL3P	152m/500ft Box		
14/4P	14	4 Cond/19 Str BC, LS-PVC	LS-PVC - White	UL FPLP, CL3P	305m/1000ft Spool		
14/4P-BK	14	4 Cond/19 Str BC, LS-PVC	LS-PVC - White	UL FPLP, CL3P	305m/1000ft Spool		
12/2P	12	2 Cond/19 Str BC, LS-PVC	LS-PVC - White	UL FPLP, CL3P	305m/1000ft Spool		
<b>Plenum - Shielded</b>							
<b>SCP Part Number</b>	<b>AWG</b>	<b>Construction</b>	<b>Jacket / Color</b>	<b>Installation Rating</b>	<b>Packaged Length</b>		
22/2SHP	22	2 Cond/7 Str BC, LS-PVC, AL Mylar, Drain	LS-PVC/White	UL CMP	305m/1000ft Spool		
22/4SHP	22	4 Cond/7 Str BC, LS-PVC, AL Mylar, Drain	LS-PVC/White	UL CMP	305m/1000ft Spool		
22/4SHP-500	22	4 Cond/7 Str BC, LS-PVC, AL Mylar, Drain	LS-PVC/White	UL CMP	152m/500ft Box		
22/6SHP	22	6 Cond/7 Str BC, LS-PVC, AL Mylar, Drain	LS-PVC/White	UL CMP	305m/1000ft Spool		
22/6SHP-500	22	6 Cond/7 Str BC, LS-PVC, AL Mylar, Drain	LS-PVC/White	UL CMP	152m/500ft Box		
18/2SHP	18	2 Cond/7 Str BC, LS-PVC, AL Mylar, Drain	LS-PVC/White	UL CMP	305m/1000ft Spool		
18/4SHP	18	4 Cond/7 Str BC, LS-PVC, AL Mylar, Drain	LS-PVC/White	UL CMP	305m/1000ft Spool		
18/4SHP-500	18	4 Cond/7 Str BC, LS-PVC, AL Mylar, Drain	LS-PVC/White	UL CMP	152m/500ft Box		
18/6SHP	18	6 Cond/7 Str BC, LS-PVC, AL Mylar, Drain	LS-PVC/White	UL CMP	305m/1000ft Spool		
18/8SHP	18	8 Cond/7 Str BC, LS-PVC, AL Mylar, Drain	LS-PVC/White	UL CMP	305m/1000ft Spool		
16/2SHP	16	2 Cond/19 Str BC, LS-PVC, AL Mylar, Drain	LS-PVC/White	UL CMP	305m/1000ft Spool		
16/4SHP	16	4 Cond/19 Str BC, LS-PVC, AL Mylar, Drain	LS-PVC/White	UL CMP	305m/1000ft Spool		
<b>Security &amp; Burglar Alarm Cables</b>							
<b>Security Coil Packs</b>							
<b>Features:</b> Stranded or Solid Bare Copper Conductors, Insulated Twisted Pair; UL Listed; Descending Feet and Zone/Outlet Jkt Markings				<b>Compliance:</b> UL CMR CL2R/CL3R, c(UL) CMR FT4 75C; UL 444; NEC Article 725; RoHS; 300V 75°			
<b>Applications:</b> Low Voltage Security Systems; Intercom Systems; Sound/Audio Systems; Power-Limited Controls							
<b>Stranded Copper - Non Plenum - Riser Unshielded Coil Packs</b>							
<b>SCP Part Number</b>	<b>AWG</b>	<b>Construction</b>	<b>Jacket / Color</b>	<b>Installation Rating</b>	<b>Packaged Length</b>		
22/2COIL-BE	22	2 Cond/7Str BC, PVC	PVC - Beige	UL CMR	500ft/152m Coil Pk		
22/2COIL-BK	22	2 Cond/7Str BC, PVC	PVC - Black	UL CMR	500ft/152m Coil Pk		
22/2COIL-BL	22	2 Cond/7Str BC, PVC	PVC - Blue	UL CMR	500ft/152m Coil Pk		
22/2COIL-BN	22	2 Cond/7Str BC, PVC	PVC - Brown	UL CMR	500ft/152m Coil Pk		
22/2COIL-GN	22	2 Cond/7Str BC, PVC	PVC - Green	UL CMR	500ft/152m Coil Pk		
22/2COIL-GY	22	2 Cond/7Str BC, PVC	PVC - Gray	UL CMR	500ft/152m Coil Pk		
22/2COIL-OR	22	2 Cond/7Str BC, PVC	PVC - Orange	UL CMR	500ft/152m Coil Pk		
22/2COIL-WT	22	2 Cond/7Str BC, PVC	PVC - White	UL CMR	500ft/152m Coil Pk		
22/2COIL-WT-1000	22	2 Cond/7Str BC, PVC	PVC - White	UL CMR	1000ft/305m Coil Pk		
22/2COIL-YL	22	2 Cond/7Str BC, PVC	PVC - Yellow	UL CMR	500ft/152m Coil Pk		
22/4COIL-BK	22	4 Cond/7Str BC, PVC	PVC - Black	UL CMR	500ft/152m Coil Pk		
22/4COIL-BL	22	4 Cond/7Str BC, PVC	PVC - Blue	UL CMR	500ft/152m Coil Pk		
22/4COIL-BN	22	4 Cond/7Str BC, PVC	PVC - Brown	UL CMR	500ft/152m Coil Pk		
22/4COIL-GN	22	4 Cond/7Str BC, PVC	PVC - Green	UL CMR	500ft/152m Coil Pk		
22/4COIL-GY	22	4 Cond/7Str BC, PVC	PVC - Gray	UL CMR	500ft/152m Coil Pk		
22/4COIL-OR	22	4 Cond/7Str BC, PVC	PVC - Orange	UL CMR	500ft/152m Coil Pk		
22/4COIL-WT	22	4 Cond/7Str BC, PVC	PVC - White	UL CMR	500ft/152m Coil Pk		
22/4COIL-YL	22	4 Cond/7Str BC, PVC	PVC - Yellow	UL CMR	500ft/152m Coil Pk		

**Solid Copper - Non Plenum - Riser Unshielded Coil Packs**

SCP Part Number	AWG	Construction	Jacket / Color	Installation Rating	Packaged Length
22/2SOL-COIL-BE	22	2 Cond SOL BC, PVC	PVC - Beige	UL CMR	500ft/152m Coil Pk
22/2SOL-COIL-BL	22	2 Cond SOL BC, PVC	PVC - Blue	UL CMR	500ft/152m Coil Pk
22/2SOL-COIL-BN	22	2 Cond SOL BC, PVC	PVC - Brown	UL CMR	500ft/152m Coil Pk
22/2SOL-COIL-GN	22	2 Cond SOL BC, PVC	PVC - Green	UL CMR	500ft/152m Coil Pk
22/2SOL-COIL-GY	22	2 Cond SOL BC, PVC	PVC - Gray	UL CMR	500ft/152m Coil Pk
22/2SOL-COIL-WT	22	2 Cond SOL BC, PVC	PVC - White	UL CMR	500ft/152m Coil Pk
22/2SOL-COIL-YL	22	2 Cond SOL BC, PVC	PVC - Yellow	UL CMR	500ft/152m Coil Pk
22/4SOL-COIL-BE	22	4 Cond SOL BC, PVC	PVC - Beige	UL CMR	500ft/152m Coil Pk
22/4SOL-COIL-GN	22	4 Cond SOL BC, PVC	PVC - Green	UL CMR	500ft/152m Coil Pk
22/4SOL-COIL-WT	22	4 Cond SOL BC, PVC	PVC - White	UL CMR	500ft/152m Coil Pk
22/4SOL-COIL-YL	22	4 Cond SOL BC, PVC	PVC - Yellow	UL CMR	500ft/152m Coil Pk

**Security & Burglar Alarm Non-Plenum**

**Features:** Stranded or Solid Bare Copper Conductors, Insulated Twisted Pair; UL Listed; Descending Feet and Zone/Outlet Jkt Markings  
**Compliance:** UL CMR CL2R/CL3R, c(UL) CMR FT4 75C; UL 444; NEC Article 725; RoHS; 300V 75°  
**Applications:** Low Voltage Security Systems; Intercom Systems; Sound/Audio Systems; Power-Limited Controls

**Non-Plenum - Riser Unshielded**

SCP Part Number	AWG	Construction	Jacket / Color	Installation Rating	Packaged Length
22/2-GY	22	2 Cond/7Str BC, PVC	PVC - Gray	UL CMR	305m/1000ft Box
22/2-WT	22	2 Cond/7Str BC, PVC	PVC - White	UL CMR	305m/1000ft Box
22/2-WT-500	22	2 Cond/7Str BC, PVC	PVC - White	UL CMR	152m/500ft Box
22/2ZIP-1000	22	2 Cond/7Str BC, PVC	ZIP PVC - White	UL CMR	305m/1000ft Box
22/2SOL-WT	22	2 Cond/SOL BC, PVC	PVC - White	UL CMR	305m/1000ft Box
22/2SOL-WT-500	22	2 Cond/SOL BC, PVC	PVC - White	UL CMR	152m/500ft Box
22/4-GY	22	4 Cond/7 Str BC, PVC	PVC - Gray	UL CMR	305m/1000ft Box
22/4-GY-500	22	4 Cond/7 Str BC, PVC	PVC - Gray	UL CMR	152m/500ft Box
22/4-WT	22	4 Cond/7 Str BC, PVC	PVC - White	UL CMR	305m/1000ft Box
22/4-WT-500	22	4 Cond/7 Str BC, PVC	PVC - White	UL CMR	152m/500ft Box
22/4SOL-BK-500	22	4 Cond/SOL BC, PVC	PVC - Black	UL CMR	152m/500ft Box
22/4SOL-BN	22	4 Cond/SOL BC, PVC	PVC - Brown	UL CMR	305m/1000ft Box
22/4SOL-BN-500	22	4 Cond/SOL BC, PVC	PVC - Brown	UL CMR	152m/500ft Box
22/4SOL-WT	22	4 Cond/SOL BC, PVC	PVC - White	UL CMR	305m/1000ft Box
22/4SOL-WT-500	22	4 Cond/SOL BC, PVC	PVC - White	UL CMR	152m/500ft Box
22/6-GY	22	6 Cond/7 Str BC, PVC	PVC - Gray	UL CMR	305m/1000ft Box
22/6-GY-500	22	6 Cond/7 Str BC, PVC	PVC - Gray	UL CMR	152m/500ft Box
22/6-WT	22	6 Cond/7 Str BC, PVC	PVC - White	UL CMR	305m/1000ft Box
22/8-GY	22	8 Cond/7 Str BC, PVC	PVC - Gray	UL CMR	305m/1000ft Box
22/8-GY-500	22	8 Cond/7 Str BC, PVC	PVC - Gray	UL CMR	152m/500ft Box
22/10-500	22	10 Cond/7 Str BC, PVC	PVC - White	UL CMR	152m/500ft Spool
22/12-500	22	12 Cond/7 Str BC, PVC	PVC - White	UL CMR	152m/500ft Box

**Non-Plenum - Riser Shielded**

SCP Part Number	AWG	Construction	Jacket / Color	Installation Rating	Packaged Length
22/2SH-GY	22	2 Cond/7 Str BC, PVC, AL Foil, Drain	PVC - Gray	UL CMR	305m/1000ft Box
22/4SH-GY	22	4 Cond/7 Str BC, PVC, AL Foil, Drain	PVC - Gray	UL CMR	305m/1000ft Box
22/4SH-GY-500	22	4 Cond/7 Str BC, PVC, AL Foil, Drain	PVC - Gray	UL CMR	152m/500ft Box
22/6SH-GY	22	6 Cond/7 Str BC, PVC, AL Foil, Drain	PVC - Gray	UL CMR	305m/1000ft Box
22/6SH-500	22	6 Cond/7 Str BC, PVC, AL Foil, Drain	PVC - Gray	UL CMR	152m/500ft Box
22/6SH-WT	22	6 Cond/7 Str BC, PVC, AL Foil, Drain	PVC - Gray	UL CMR	305m/1000ft Box
22/8SH-GY	22	8 Cond/7 Str BC, PVC, AL Foil, Drain	PVC - Gray	UL CMR	305m/1000ft Box
22/8SH-WT	22	8 Cond/7 Str BC, PVC, AL Foil, Drain	PVC - Gray	UL CMR	305m/1000ft Box

**Security & Burglar Alarm Plenum**

**Features:** Stranded or Solid Bare Copper Conductors, Insulated Twisted Pair; UL Listed; Descending Feet and Zone/Outlet Jkt Markings; Packaging: Spool or Box  
**Compliance:** Plenum: UL CMP CL2P/CL3P, c(UL) FT6 75C; UL 444; NEC Article 725; RoHS; 300V 75°  
**Applications:** Low Voltage Security Systems Routed in Plenum Spaces; Intercom Systems; Sound/Audio Systems; Power-Limited Controls

**Plenum - UnShielded**

SCP Part Number	AWG	Construction	Jacket / Color	Installation Rating	Packaged Length		
22/2P	22	2 Cond/7 Str BC, LS-PVC	LS-PVC/White	UL CMP	305m/1000ft Box		
22/4P	22	4 Cond/7 Str BC, LS-PVC	LS-PVC/White	UL CMP	305m/1000ft Box		
22/4P-500	22	4 Cond/7 Str BC, LS-PVC	LS-PVC/White	UL CMP	152m/500ft Box		
22/6P	22	6 Cond/7 Str BC, LS-PVC	LS-PVC/White	UL CMP	305m/1000ft Spool		
22/6P-500	22	6 Cond/7 Str BC, LS-PVC	LS-PVC/White	UL CMP	152m/500ft Box		
22/12P	22	12 Cond/7 Str BC, LS-PVC	LS-PVC/White	UL CMP	305m/1000ft Spool		
<b>Plenum - Shielded</b>							
SCP Part Number	AWG	Construction	Jacket / Color	Installation Rating	Packaged Length		
22/2SHP	22	2 Cond/7 Str BC, LS-PVC, AL Mylar, Drain	LS-PVC/White	UL CMP	305m/1000ft Spool		
22/4SHP	22	4 Cond/7 Str BC, LS-PVC, AL Mylar, Drain	LS-PVC/White	UL CMP	305m/1000ft Spool		
22/4SHP-500	22	4 Cond/7 Str BC, LS-PVC, AL Mylar, Drain	LS-PVC/White	UL CMP	152m/500ft Box		
22/6SHP	22	6 Cond/7 Str BC, LS-PVC, AL Mylar, Drain	LS-PVC/White	UL CMP	305m/1000ft Spool		
22/6SHP-500	22	6 Cond/7 Str BC, LS-PVC, AL Mylar, Drain	LS-PVC/White	UL CMP	152m/500ft Box		
<b>Speaker Cables</b>							
<b>Pro Grade Indoor/Outdoor HD Series - Commercial and Residential</b>							
<b>Features:</b> Highly Flexible. Indoor/Outdoor Rated. High Strand Count Oxygen Free Copper (OFC); Unshielded; Insulated twisted pair; HD UV Sun Res PVC Jacket; Easy Strip Round Rope Lay Construction; SCP Tangle Free Reelex II Box; Descending Feet and Zone/Outlet Jkt Markings			<b>Compliance:</b> UL CMR CL2R/CL3R c(UL) FT4; RoHS; Low Voltage & Power Limited Systems; 300V 75°C				
<b>Applications:</b> Commercial & Residential; High Definition; Home Theater Systems, In-Wall Speakers; Class 2/3 Low Voltage Power; UL Direct Burial; Outdoor: UV Sun Resistant ; Indoor: In-Wall Riser Rated							
SCP Part Number	AWG	Construction	Jacket / Color	Installation Rated	Packaging		
16/2OFC-HD-BK	16	2 Cond/65 Str OFC, PVC	HD UV-PVC - Black	UL CMR	152m/500ft Pull Box		
16/2OFC-HD-PUR	16	2 Cond/65 Str OFC, PVC	HD UV-PVC - Purple	UL CMR	152m/500ft Pull Box		
16/2OFC-HD-WT	16	2 Cond/65 Str OFC, PVC	HD UV-PVC - White	UL CMR	152m/500ft Pull Box		
16/4OFC-HD-BK	16	4 Cond/65 Str OFC, PVC	HD UV-PVC - Black	UL CMR	152m/500ft Pull Box		
16/4OFC-HD-PUR	16	4 Cond/65 Str OFC, PVC	HD UV-PVC - Purple	UL CMR	152m/500ft Pull Box		
16/4OFC-HD-WT	16	4 Cond/65 Str OFC, PVC	HD UV-PVC - White	UL CMR	152m/500ft Pull Box		
14/2OFC-HD-BK	14	2 Cond/105 Str OFC, PVC	HD UV-PVC - Black	UL CL3R	152m/500ft Pull Box		
14/2OFC-HD-PUR	14	2 Cond/105 Str OFC, PVC	HD UV-PVC - Purple	UL CL3R	152m/500ft Pull Box		
14/2OFC-HD-WT	14	2 Cond/105 Str OFC, PVC	HD UV-PVC - White	UL CL3R	152m/500ft Pull Box		
14/4OFC-HD-BK	14	4 Cond/105 Str OFC, PVC	HD UV-PVC - Black	UL CL3R	152m/500ft Reel in Box		
14/4OFC-HD-PUR	14	4 Cond/105 Str OFC, PVC	HD UV-PVC - Purple	UL CL3R	152m/500ft Reel in Box		
14/4OFC-HD-WT	14	4 Cond/105 Str OFC, PVC	HD UV-PVC - White	UL CL3R	152m/500ft Reel in Box		
12/2OFC-HD-BK	12	2 Cond/65 Str OFC, PVC	HD UV-PVC - Black	UL CL3R	152m/500ft Reel in Box		
12/2OFC-HD-WT	12	2 Cond/65 Str OFC, PVC	HD UV-PVC - White	UL CL3R	152m/500ft Reel in Box		
12/4OFC-HD-WT	12	4 Cond/65 Str OFC, PVC	HD UV-PVC - White	UL CL3R	152m/500ft Spool		
<b>In-Wall Series</b>							
High Strand Count Oxygen Free Copper Speaker Cable with Smaller Cable OD for Easy Installation When Bundling through Conduit							
<b>Features:</b> Highly Flexible with Minimum OD. High Strand Count Oxygen Free Copper; Unshielded; Insulated twisted pair BK/RD & BK/RD/GN/WT; Easy Strip PVC Jkt; Smaller OD ideal for conduit. SCP Tangle Free Reelex II Box; Descending Feet and Zone/Outlet Jacket Markings			<b>Compliance:</b> UL CMR CL2R/CL3R c(UL) FT4; RoHS; Low Voltage & Power Limited Systems; 300V 75°C; 14-12AWG are not recognized by c(UL).				
<b>Applications:</b> Commercial & Residential; High Definition; Home Theater Systems, In-Wall Speakers; Class 2/3 Low Voltage Power; In-Wall Riser Rated							
SCP Part Number	AWG	Construction	Jacket / Color	Installation Rated	Packaging		
16/2OFC-BK	16	2 Cond/65 Str OFC, PVC	PVC - Black	UL CMR/CL3R	500ft Pull Box		
16/2OFC-PUR	16	2 Cond/65 Str OFC, PVC	PVC - Purple	UL CMR/CL3R	500ft Pull Box		
16/2OFC-PUR-1000	16	2 Cond/65 Str OFC, PVC	PVC - Purple	UL CMR/CL3R	1000ft Pull Box		
16/2OFC-WT	16	2 Cond/65 Str OFC, PVC	PVC - White	UL CMR/CL3R	500ft Pull Box		
16/2OFC-WT-1000	16	2 Cond/65 Str OFC, PVC	PVC - White	UL CMR/CL3R	1000ft Pull Box		
16/2OFC-WT-HDBX	16	2 Cond/65 Str OFC, PVC	PVC - White	UL CMR/CL3R	500ft Heavy Duty Box		
16/2OFC-WT-HDBX-1000	16	2 Cond/65 Str OFC, PVC	PVC - White	UL CMR/CL3R	1000ft Heavy Duty Box		
16/4OFC-BK	16	4 Cond/65 Str OFC, PVC	PVC - White	UL CMR/CL3R	500ft Pull Box		
16/4OFC-OR	16	4 Cond/65 Str OFC, PVC	PVC - White	UL CMR/CL3R	500ft Pull Box		
16/4OFC-PUR	16	4 Cond/65 Str OFC, PVC	PVC - Purple	UL CMR/CL3R	500ft Pull Box		
16/4OFC-WT	16	4 Cond/65 Str OFC, PVC	PVC - White	UL CMR/CL3R	500ft Pull Box		
14/2OFC-BK	14	2 Cond/105 Str OFC, PVC	PVC - Black	UL CL3R	500ft Pull Box		

14/2OFC-PUR	14	2 Cond/105 Str OFC, PVC	PVC - Purple	UL CL3R	500ft Pull Box		
14/2OFC-WT	14	2 Cond/105 Str OFC, PVC	PVC - White	UL CL3R	500ft Pull Box		
14/4OFC-BK	14	4 Cond/105 Str OFC, PVC	PVC - Black	UL CL3R	500ft Reel-In-Box		
14/4OFC-PUR	14	4 Cond/105 Str OFC, PVC	PVC - Purple	UL CL3R	500ft Reel-In-Box		
14/4OFC-WT	14	4 Cond/105 Str OFC, PVC	PVC - White	UL CL3R	500ft Reel-In-Box		
12/2OFC-WT	12	2 Cond/65 Str OFC, PVC	PVC - White	UL CL3R	500ft Reel-In-Box		
12/4OFC-WT	12	4 Cond/65 Str OFC, PVC	PVC - White	UL CL3R	500ft Spool		
<b>Low Smoke Zero Halogen Commercial/Residential Series</b>							
High Strand Count Oxygen Free Copper Speaker Cable - Flexible Indoor Rated LSZH Jacket							
<b>Features:</b> High Strand Count Oxygen Free Copper; Unshielded; Insulated twisted pair; Easy Strip LSZH Jacket; SCP Tangle Free Reel II Box; Descending Feet and SCP Zone/Outlet Jacket Markings				<b>Compliance:</b> Low Smoke Zero Halogen, IEC 60332-1-2; Low Voltage & Power Limited Systems; 300V 75°C; RoHS			
<b>Applications:</b> Commercial & Residential; High Definition; Home Theater Systems, In-Wall Speakers; Class 2/3 Low Voltage Power; Marine							
<b>SCP Part Number</b>	<b>AWG</b>	<b>Construction</b>	<b>Jacket / Color</b>	<b>Installation Rated</b>	<b>Packaging</b>		
16/2OFC-LSZH-WT	16	2 Cond/65 Str OFC, PVC	LSZH - White	In-Wall & Marine	152m/500ft Pull Box		
14/2OFC-LSZH-PUR	14	2 Cond/105 Str OFC, PVC	LSZH - Purple	In-Wall & Marine	152m/500ft Pull Box		
14/2OFC-LSZH-WT	14	2 Cond/105 Str OFC, PVC	LSZH - White	In-Wall & Marine	152m/500ft Pull Box		
<b>Contractor Series</b>							
Contractor Grade Speaker Cables for Standard Installations							
<b>Features:</b> Oxygen Free Copper; Unshielded; Insulated twisted pair; Easy Strip PVC Jacket; SCP Tangle Free Reel II Box; Descending Meter and SCP Zone/Outlet Jacket				<b>Compliance:</b> UL CMR CL2R/3R c(UL) FT4; RoHS; Low Voltage & Power Limited Systems; 300V 75°C			
<b>Applications:</b> Residential; Speaker, Audio, Control; In-Wall Speakers; Class 2/3 Low Voltage Power							
<b>SCP Part Number</b>	<b>AWG</b>	<b>Construction</b>	<b>Jacket / Color</b>	<b>Installation Rated</b>	<b>Packaging</b>		
16/2SP-26-BL	16	2 Cond/26 Str OFC, PVC	PVC - Blue	UL CMR/CL3R	500ft Pull Box		
16/2SP-26-WT	16	2 Cond/26 Str OFC, PVC	PVC - White	UL CMR/CL3R	500ft Pull Box		
16/2SP-26-WT-1000	16	2 Cond/26 Str OFC, PVC	PVC - White	UL CMR/CL3R	1000ft Pull Box		
16/2SP-65-PUR-1000	16	2 Cond/26 Str OFC, PVC	PVC - Purple	UL CMR/CL3R	1000ft Pull Box		
16/4SP-26-BL	16	4 Cond/26 Str OFC, PVC	PVC - Blue	UL CMR/CL3R	500ft Pull Box		
16/4SP-26-WT	16	4 Cond/26 Str OFC, PVC	PVC - White	UL CL3R	500ft Pull Box		
14/2SP-41-YL	14	2 Cond/41 Str OFC, PVC	PVC - Yellow	UL CL3R	500ft Pull Box		
14/2SP-41-YL-1000	14	2 Cond/41 Str OFC, PVC	PVC - Yellow	UL CL3R	1000ft Spool		
14/4SP-41-YL	14	4 Cond/41 Str OFC, PVC	PVC - Yellow	UL CL3R	500ft Reel in Box		
<b>Direct Burial Cables</b>							
<b>Landscape / Direct Burial ProSeries Speaker Cables</b>							
Professionals Choice for All High Performance Landscape and Outdoor Speaker Systems. Retains Flexibility in All Outdoor Environments. ProSeries Landscape/Direct Burial cables feature LLDPE (Linear Low-Density Polyethylene) jackets that provide superior performance and durability over PVC or standard PE jacket cables. These cables also are UV Sun Resistant and retains flexible performance in both hot and cold environments.							
<b>Features:</b> High Strand Count Oxygen Free Copper; Unshielded; Insulated twisted pair; LLDPE Jacket; Waterproof: Gel Filled; Superior Durability and Longevity; Rodent Resistant; UV Sun Resistant; Descending Feet Markings				<b>Compliance:</b> UL 444, NEC CL3, RoHS			
<b>Applications:</b> Professional Outdoor Speaker Systems; Direct Burial Waterproof; Audio/Security/Control; Class 2/3 Low Voltage Power; Installs in Wet Environments; Commercial/Residential/Institutional							
<b>SCP Part Number</b>	<b>AWG</b>	<b>Construction</b>	<b>Jacket / Color</b>	<b>Installation Rating</b>	<b>Packaged Length</b>		
14/2SP-DB-500	14	2 Cond/105 Str OFC, PVC, Gel Fill	LLDPE - Black	Direct Burial/UV Outdoor	152m/500ft Spool		
14/4SP-DB-GEL	14	4 Cond/105 Str OFC, PVC, Gel Fill	LLDPE - Black	Direct Burial/UV Outdoor	305m/1000ft Spool		
14/4SP-DB-GEL-500	14	4 Cond/105 Str OFC, PVC, Gel Fill	LLDPE - Black	Direct Burial/UV Outdoor	152m/500ft Spool		
<b>Direct Burial - Multi-Purpose</b>							
<b>Features:</b> LLDPE jacket with UV Sun Resistance. Insulated Twisted Pair; Water Block Tape (WBT) for moisture protection; Descending Feet and Zone/Outlet Jkt Markings; Packaging: Spool				<b>Compliance:</b> UL 444, NEC CL3, RoHS			
<b>Applications:</b> Direct Burial; Outdoor; Outdoor Speaker; Low Voltage Class 2/3, Security Systems; Intercom Systems; Speaker/Audio Systems; Power-Limited Controls							
<b>Unshielded Direct Burial - Multi-Purpose</b>							
<b>SCP Part Number</b>	<b>AWG</b>	<b>Construction</b>	<b>Jacket / Color</b>	<b>Installation Rating</b>	<b>Packaged Length</b>		
18/2DB-500	18	2 Cond/16 Str BC, PVC, WBT	LLDPE-Black	Direct Burial/Outdoor	152m/500ft Spool		
16/2DB	16	2 Cond/16 Str BC, PVC, WBT	LLDPE-Black	Direct Burial/Outdoor	305m/1000ft Spool		
16/4DB	16	4 Cond/16 Str BC, PVC, WBT	LLDPE-Black	Direct Burial/Outdoor	305m/1000ft Spool		

16/4DB-500	16	4 Cond/16 Str BC, PVC, WBT	LLDPE-Black	Direct Burial/Outdo	152m/500ft Spool		
14/4DB	14	4 Cond/105 Str BC, PVC, WBT	LLDPE-Black	Direct Burial/Outdo	305m/1000ft Spool		
14/4DB-500	14	4 Cond/105 Str BC, PVC, WBT	LLDPE-Black	Direct Burial/Outdo	152m/500ft Spool		
<b>Shielded Direct Burial - Multi-Purpose</b>							
SCP Part Number	AWG	Constuction	Jacket / Color	Installation Rating	Packaged Length		
18/2SHDB	18	2 Cond/16 Str BC, PVC, AL Foil, Drain, WBT	LLDPE-Black	Direct Burial/Outdo	305m/1000ft Spool		
18/4SHDB	18	4 Cond/16 Str BC, PVC, AL Foil, Drain, WBT	LLDPE-Black	Direct Burial/Outdo	305m/1000ft Spool		
18/6SHDB	18	6 Cond/16 Str BC, PVC, AL Foil, Drain, WBT	LLDPE-Black	Direct Burial/Outdo	305m/1000ft Spool		
16/2SHDB	16	2 Cond/65 Str BC, PVC, AL Foil, Drain, WBT	LLDPE-Black	Direct Burial/Outdo	305m/1000ft Spool		
16/2SHDB-500	16	2 Cond/65 Str BC, PVC, AL Foil, Drain, WBT	LLDPE-Black	Direct Burial/Outdo	152m/500ft Spool		
14/2SHDB	14	2 Cond/105 Str BC, PVC, AL Foil, Drain, WBT	LLDPE-Black	Direct Burial/Outdo	305m/1000ft Spool		
14/2SHDB-500	14	2 Cond/105 Str BC, PVC, AL Foil, Drain, WBT	LLDPE-Black	Direct Burial/Outdo	152m/500ft Spool		
12/2SHDB	12	2 Cond/65 Str BC, PVC, AL Foil, Drain, WBT	LLDPE-Black	Direct Burial/Outdo	305m/1000ft Spool		
<b>Direct Burial - Category/LAN Cables</b>							
SCP Cat6 Direct Burial cables feature LLDPE (Linear Low-Density Polyethylene) jackets that provide superior performance over PVC or standard PE jacket cables. These cables also are UV Sun Resistant and retain flexible performance in both hot and cold environments.							
<b>Features:</b> LLDPE Jacket, Moisture Protection and UV Sun Resistant; Descending FT and Zone/Outlet Jkt Markings; Limited Lifetime Warranty				<b>Compliance:</b> ANSI/TIA 568.2-D; ISO/IEC 11801; IEEE 802.3bt; RoHS			
<b>Applications:</b> High performance IT, LAN & Ethernet installations. Suitable for use in all outdoor and direct burial structured wiring systems according to cable classification. PoE Compliant							
SCP Part Number	AWG	Construction	Jacket / Color	Installation Rating	Packaged Length		
<b>Cat6a :</b>							
CAT6A-U/FTP-DB	23	4pr U/FTP SOL BC / SFPE	LLDPE - Black	Direct Burial/Outdo	305m/1000ft Spool		
<b>Cat6 :</b>							
CAT6-DB	23	4pr U/UTP SOL BC / HDPE	LLDPE - Black	Direct Burial/UV Outdo	305m/1000ft Spool		
CAT6SH-DB	23	4pr F/UTP SOL BC / HDPE	LLDPE - Black	Direct Burial/UV Outdo	305m/1000ft Spool		
CAT6SH-OUT	23	4pr F/UTP SOL BC / HDPE	LLDPE - Black	UV Outdoor	305m/1000ft Spool		
<b>Cat5e :</b>							
CAT5E-25PR-DB	24	25pr U/UTP SOL BC / HDPE	LLDPE - Black	Direct Burial/UV Outdo	305m/1000ft Spool		
CAT5E-DB	24	4pr U/UTP SOL BC / FEP	LLDPE - Black	Direct Burial/UV Outdo	305m/1000ft Spool		
CAT5E-DB-500	24	4pr U/UTP SOL BC / FEP	LLDPE - Black	Direct Burial/UV Outdo	152m/500ft Spool		
CAT5E-SH-DB	24	4pr F/UTP SOL BC / HDPE	LLDPE - Black	Direct Burial/UV Outdo	305m/1000ft Spool		
<b>Structured - Composite Cables</b>							
<b>Features:</b> Smart home wiring composite cables. One Pull/One Drop convenience. Protects component cables from installation damage. UL Rated. Descending FT and				<b>Compliance:</b> UL CM CL2/3, c(UL) FT4 75C; 300V; RoHS; UL 444; ANSI/TIA 568.2-D; ISO/IEC 11801			
<b>Applications:</b> Structured Cabling Installations. Horizontal LAN Ethernet. CATV/SATV, Audio/Video/Control. Power Limited Class 2/3.							
SCP Part Number	Construction	Jacket / Color	Installation Rating	Packaged Length			
HNC-1-BL	1x Cat5e UTP 24AWG SOL BC + 1x RG6/U BC Quad Shield Coax, Siamese (Side x Side)	PVC - Blue	UL CM FT4	152m/500ft Spool			
HNC-1-WT	1x Cat5e UTP 24AWG SOL BC + 1x RG6/U BC Quad Shield Coax, Siamese (Side x Side)	PVC - White	UL CM FT4	152m/500ft Spool			
HNC-1-1000-BL	1x Cat5e UTP 24AWG SOL BC + 1x RG6/U BC Quad Shield Coax, Siamese (Side x Side)	PVC - Blue	UL CM FT4	305m/1000ft Spool			
HNC-2	2x Cat5e UTP 24AWG SOL BC + 2x RG6/U CCS Quad Shield Coax, Bundled	PVC - Blue	UL CM FT4	152m/500ft Spool			
HNC-2-BC	2x Cat5e UTP 24AWG SOL BC + 2x RG6/U BC Quad Shield Coax, Bundled	PVC - Blue	UL CM FT4	152m/500ft Spool			
HNC-3	2x Cat5e UTP 24AWG SOL BC + 2x RG6/U BC Quad Shield Coax + 2x OM1 MM 62.5/125 Fiber, Bundled	PVC - Purple	UL CM FT4	152m/500ft Spool			close-out
HNC-4	1x Cat5e UTP 24AWG SOL BC + 1x 4C/16AWG 65 Str OFC Speaker Cable, Siamese (Side x Side)	PVC - Purple	UL CM FT4	152m/500ft Spool			close-out
HNC-5	1x Cat5e UTP 24AWG SOL BC + 2x RG6/U BC Quad Shield Coax, Triamese (Side x Side)	PVC - Gray	UL CM FT4	152m/500ft Spool			close-out
HNC-6	2x Cat5e UTP 24AWG SOL BC + 1x RG6/U BC Quad Shield Coax, Triamese (Side x Side)	PVC - Blue	UL CM FT4	152m/500ft Spool			
HNC-8	2x Cat6 UTP 23AWG SOL BC + 2x RG6/U BC Quad Shield Coax, Bundled	PVC - Blue	UL CM FT4	152m/500ft Spool			
HNC-9	2x Cat6 UTP 23AWG SOL BC + 1x Cat5e UTP 24AWG SOL BC + 2x RG6/U BC Quad Shield Coax, Bundled	PVC - Blue	UL CM FT4	152m/500ft Spool			close-out
HNC-10	4x Cat5e UTP 24AWG SOL BC, Bundled	PVC - Black	UL CM FT4	152m/500ft Spool			

HNC-11	4x Cat6 UTP 23AWG SOL BC, Bundled	PVC - Black	UL CM FT4	152m/500ft Spool		
HNC-12	2x Cat6 UTP 23AWG SOL BC + 2x RG6/U BC Quad Shield Coax + 2x OM1 MM 62.5/125 Fiber, Bundled	PVC - Blue	UL CM FT4	152m/500ft Spool		
HNC-15	1x Cat6 UTP 23AWG SOL BC + 1x RG6/U BC Quad Shield Coax, Siamese (Side x Side)	PVC - Blue	UL CM FT4	305m/1000ft Spool		
HNC-16	3x Cat5e UTP 24AWG SOL BC + 1x RG6/U Quad Shield Coax, Bundled	PVC - Blue	UL CM FT4	152m/500ft Spool		
HNC-18	3x Cat6 UTP 23AWG SOL BC + 1x RG6/U BC Quad Shield Coax, Bundled	PVC - Blue	UL CM FT4	152m/500ft Spool		