


# KPM-35 & KLS-35

Optical Power Meter & Light Source



## Key Features

- High Precision
- Highly accurate unit offering 6 calibrated wavelengths
- Interchangeable connectors
- Durable and reliable design
- Easy-to-use interface for error-free testing
- Rubber armor protection



Backlight  
display



One  
key start



Automatic  
shutdown



Plug  
and play



6 calibrated  
wavelengths



Silica gel  
protect pads

# PRODUCT FEATURES



Drop proof



Hand-held



Bracket



Rubber protection

## KPM-35



Interface accessories



SC



FC



ST

|                     |  |
|---------------------|--|
| Wavelength(nm)      | 800~1700nm   |
| Measurement Range   | -70+3dBm / -50~+26dBm  |
| Optical Connector   | FC+SC+ 2.5mm universal (1.25mm for LC is Optional)           |
| Power Supply        | Alkaline Battery(3 AA 1.5V batteries) (Purchased separately) |
| Display Units       | dB / dBm / w   |
| Resolution (dB)     | 0.01   |
| Dimensions / Weight | 160x85x45mm / 220 g  |

# KLS-35



Interface accessories



SC



FC



ST

|                        |  |
|------------------------|--|
| Wavelength(nm)         | SM 1310/1550nm (KLS-35S)                                     |
|                        | MM 850/1300/1310/1550nm (KLS-35MS)                           |
|                        | PON 1310/1490/1550nm (KLS-35P)                               |
| Typical Output Power   | -5dB   |
| Optical Connector      | FC+SC+ 2.5mm universal (1.25mm for LC is Optional)           |
| Power Supply           | Alkaline Battery(3 AA 1.5V batteries) (Purchased separately) |
| Output Stability       | ±0.05dB/15mins; ±0.1dB/ 8hours                               |
| Modulation Frequencies | CW,270Hz,1KHz,2KHz   |
| Dimensions / Weight    | 160x85x45mm / 220g   |

## PACKAGING DISPLAY:

